

# nfssex-cfr

Clea F. Rees\*

v1.3 (SVN Rev: 11042) 2025/06/22

## Abstract

`nfssex-cfr` is an extension and modification of Philipp Lehman's `nfssex` which provides extended font selection commands modelled on those provided by  $\text{\LaTeX} 2_{\epsilon}$ . Given an appropriate font configuration, `nfssex-cfr` enables users to change the weight, width, shape and style of font as easily as they can select bold, italic or typewriter. For instance, the package makes it trivial to use proportional, hanging figures in the body of the text, proportional, lining figures in captions and headers and tabular, lining figures in tables. An extensive choice of commands are provided to access a wide variety of weights, widths, shapes and styles from the more common (e.g. semi-bold or condensed) to the less common (e.g. 'outline' and right or upright italic). Comprehensive support is provided for 'swash' and 'alternate' styles. These are implemented as families rather than shapes to support fonts which offer multiple swash shapes (e.g. small-caps, italic and upright) or alternate styles. These may be used to provide effective access to fancy ligatures, end-of-word swashes etc. without sacrificing the range of characters provided by `T1`.

The package also provides code to enable new font definition files, which may use `\DeclareEncodingSubset` as of the 2024-11-19  $\text{\LaTeX}$  release, to be used with older versions of the format. For post-2020 versions of the format, the package supports these declarations; for older versions, the package provides an empty definition.

The package is not primarily intended for direct use by end-users, but is designed rather to facilitate the creation of more sophisticated font support packages. End-users may nonetheless find the package useful, subject to the constraints explained in this document. Moreover, end-users may wish to pass options to the package on newer kernels, if loading font support packages which have not been updated for changes to font selection<sup>1</sup>.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Macros</b>	<b>3</b>

---

\*Bug tracker: [codeberg.org/cfr/nfssex/issues](https://codeberg.org/cfr/nfssex/issues) | Code: [codeberg.org/cfr/nfssex](https://codeberg.org/cfr/nfssex) | Mirror: [github.com/cfr42/nfssex](https://github.com/cfr42/nfssex)

<sup>1</sup>'Kernel' refers to the  $\text{\LaTeX}$  kernel in this context and should not be confused with your system kernel.

<b>3</b>	<b>Newer L<sup>A</sup>T<sub>E</sub>X Kernels</b>	<b>7</b>
3.1	Required Changes to Font Support Files . . . . .	8
<b>4</b>	<b>Older L<sup>A</sup>T<sub>E</sub>X Kernels</b>	<b>10</b>
<b>5</b>	<b>Bugs, Non-Bugs &amp; Debugging</b>	<b>10</b>
<b>6</b>	<b>Implementation</b>	<b>11</b>
6.1	Main package file . . . . .	11
6.2	NNFSS . . . . .	17
6.3	NFSS . . . . .	37

## List of Tables

1	Standard (kernel) macros (re)defined . . . . .	4
2	Standard (kernel) font change rules redefined . . . . .	4
3	Family switches: general . . . . .	5
4	Family switches: figures . . . . .	5
5	Shape switches . . . . .	6
6	Series switches: widths . . . . .	6
7	Series switches: weights . . . . .	7

## 1 Introduction

The package was originally a fairly simple extension of Philipp Lehman’s `nfssex`. `nfssex` provides commands which enable one to specify font features not covered by the New Font Selection Scheme (NFSS). The package developed according to the needs of particular fonts I configured for L<sup>A</sup>T<sub>E</sub>X and, in a few cases, my dissatisfaction with the original commands.

In adapting the package for the (New) New Font Selection Scheme<sup>2</sup> (NNFSS), I have tried to balance (i) backwards compatibility<sup>3</sup> for users loading updated font support packages, (ii) backwards compatibility for users loading packages which haven’t been updated and (iii) compatibility with the new features of NNFSS. I have also tried to account for the common case in which documents use combinations of fonts from different packages, each of which may or may not load `nfssex-cfr` and may or may not have been updated for NNFSS. This has inevitably required some compromises and there are certainly places where I would do things differently if starting from scratch.

<sup>2</sup>Officially, there is no such designation, but I have to call it something. Throughout this document and packages which depend upon it, I use this term to refer to the font selection features introduced into L<sup>A</sup>T<sub>E</sub>X in 2020.

<sup>3</sup>Note that 100% backwards compatibility cannot be implemented on current L<sup>A</sup>T<sub>E</sub>X kernels.

While I don't recommend installing this version of `nfssect-cfr` on an older system, the package should continue to work more-or-less as it always did on older kernels. To achieve this, the package is split into a main file, `nfssect-cfr.sty`, which provides common code and figures out whether to load code for NFSS (`nfssect-cfr-nfss.sty`) or NNFSS (`nfssect-sty-nfss.sty`). `nfssect-cfr-nfss.sty` is essentially what was `nfssect-cfr.sty` minus the code retained in the latter.

Unfortunately, it is impossible to ensure 100% backwards compatibility with recent L<sup>A</sup>T<sub>E</sub>X kernels. By default, `nfssect-cfr` tries to interfere as little as possible with the kernel, even at the cost of backwards compatibility. If `compat` is enabled, however, the package does its best to enable backwards compatible behaviour, at the cost of the new functionality provided by the kernel.

`nfssect-cfr` does not eschew interference with the kernel at all costs. Even without `compat` it patches or replaces some kernel code because some things just don't work sensibly<sup>4</sup>.

**All font-support code should be updated to use `compat=false` when loading `nfssect-cfr`.** The changes in NNFSS **require** changes to code based on Philipp Lehman's Font Installation Guide.

## 2 Macros

Tables 1 to 7 include macros supplied by the original `nfssect` and additions available with `nfssect-cfr`. Macros in tables 5 to 7 should work with any font definition files which more-or-less adhere to NFSS/NNFSS. This should, theoretically, be all font packages but, in practice, things are rarely so simple. Macros in tables 3 and 4 will work only with fonts named strictly according to the Berry naming scheme.

In tables 3 to 7, the third column lists the default letter codes for various font features. If the defaults are changed, the macros will try to do something different.

A + indicates that the macro will attempt to merge the addition into the current font's family name, series or shape. For example, if the current font uses oldstyle figures, the +2 indicates that `\pstyle` will attempt to select a font with figures which are both proportional and oldstyle.

A - indicates that the macro will attempt to subtract from the current font's family name, series or shape. For example, if the current font uses oldstyle figures, the -2 indicates that `\tstyle` will attempt to select a font with figures which are both tabular and oldstyle.

A comma-separated list indicates consecutive additions and/or subtraction.

<sup>4</sup>This is true in two main places. The first is the kernel's initialisation of series at the start of the document. This overwrites the default `bf` series according to the font family name rather than the font name. This means that virtual fonts which depend on Computer or Latin Modern are not handled correctly and, because this code is delayed, the problem cannot be corrected by setting things up appropriately earlier.

The second is the implementation of 'swash' which is by far the most problematic of the changes and one of the most difficult to navigate. It isn't clear to me how seriously the kernel's definition is intended to be, but I have chosen to overwrite the kernel code here.

Table 1: Standard (kernel) macros (re)defined

<code>\swshape<sup>b</sup></code>	redefined on new kernels <sup>c</sup> defined on old kernels
<code>\itshape</code>	old kernels only
<code>\scshape</code>	old kernels only
<code>\upshape</code>	old kernels only
<code>\DeclareEncodingSubset</code>	redefined on post-2020 pre-2024-11-19 kernels <sup>d</sup> defined on old kernels <sup>e</sup>

<sup>a</sup> Defined only by newer kernels.

<sup>b</sup> See tables 3 and 5 and text.

<sup>c</sup> Definition depends on kernel, `force` and `compat`.

<sup>d</sup> The redefinition is done at the beginning of the document, so does not affect any use in `.sty` files. The change allows declarations to be used in font definition files, even if the format is older than the ‘hot fix’ provided in November 2024.

<sup>e</sup> The definition is empty in this case. It enables older formats to use font definition files which include encoding declarations, but the information provided in such declarations is simply discarded.

Table 2: Standard (kernel) font change rules redefined

Shape		Applied when?
Current	Requested	
<code>it</code>	<code>sc</code>	<code>compat</code> & NNFSS only
<code>sl</code>	<code>sc</code>	<code>compat</code> & NNFSS only
<code>sc</code>	<code>it</code>	<code>compat</code> & NNFSS only
<code>sc</code>	<code>sl</code>	<code>compat</code> & NNFSS only
<code>scsl</code>	<code>it</code>	<code>compat</code> & NNFSS only

If no `+-` is used, the macro tries to select a font with the given feature without merging. For example `\sistyle` tries to switch to `si` shape regardless of the current font shape.

A `-` indicates that the macro will try to clear all relevant letter codes from the current font’s family name, series or shape. For example, `\regwidth` tries to switch to a series with no letter codes indicating non-standard widths in its name.

Additions, subtractions and clearances operate on font family names, series or shapes, as appropriate. In general, macros with `style` in their names operate on family names; those with `shape` operate on shape codes<sup>5</sup>; and those with `width` or `weight` operate on series codes.

The letter codes correspond to those specified by the NFSS specification, unless the specification does not include the relevant feature. In the latter case, I tried to choose something sensible i.e. something which made sense to me at the time. These choices are not always those specified by the NNFSS specification, since sense and sensibility are sometimes in the eye of the encoder.

One further macro is available, though it has no effect on older kernels.

`\nfssectset`  $\{\langle key-value list \rangle\}$

<sup>5</sup>But **not** `\swshape`!

Table 3: Family switches: general

Macros			
Text Command	Switch	Family Code	Style
<code>\textti</code>	<code>\tistyle</code>	+d	titling/display
<code>\textlt<sup>a</sup></code>	<code>\ltstyle<sup>b</sup></code>	+l	light if separate family
<code>\textof</code>	<code>\ofstyle</code>	+l	open-face (or outline or blank) style
<code>\textalt</code>	<code>\altstyle</code>	+a	alternative style
<code>\textreg</code>	<code>\regstyle</code>	-	regular style
<code>\emboss</code>	<code>\embosstyle</code>	+e	‘embossed’ style
<code>\textorn</code>	<code>\ornamentalstyle</code>	+p	decorative initials etc.
<code>\ornament</code>			
<code>\textqt</code>	<code>\qtstyle</code>	+q	quotation style
<code>\textsh</code>	<code>\shstyle</code>	+h	shadowed style
<code>\texttm</code>	<code>\tmstyle</code>	-s,-v,+t	monowidth typewriter
<code>\texttv</code>	<code>\tvstyle</code>	-s,-t,+v	variable width typewriter
<code>\textswash</code>	<code>\swashstyle<sup>c</sup></code>	+w	swash
<code>\textsw<sup>d</sup></code>	<code>\swshape<sup>d</sup></code>		‘find a route to swash’

<sup>a</sup> Cf. `\textlg` in table 7.

<sup>b</sup> Cf. `\lgweight` in table 7.

<sup>c</sup> Cf. `\swstyle` in table 5.

<sup>d</sup> Effect is kernel and option dependent, but potentially changes family and/or shape. ‘Tries to find a route to swash.’ See text for an explanation of what, why and when. See section 6 for details of how.

Table 4: Family switches: figures

Macros			
Text Command	Switch	Family Code	Style of Figures
<code>\textln<sup>a</sup></code>	<code>\lnstyle<sup>a</sup></code>	-	lining (cf. <code>\lstyle</code> below)
<code>\textos<sup>a</sup></code>	<code>\osstyle<sup>a</sup></code>	j	oldstyle (cf. <code>\ostyle</code> below)
<code>\textinf</code>	<code>\infstyle</code>	0	inferior
<code>\textin</code>	<code>\instyle</code>		if <code>hyperref</code> is at least v7.01m or not loaded
<code>\textsu</code>	<code>\sustyle</code>	1	superior
<code>\textl<sup>b</sup></code>	<code>\lstyle<sup>b</sup></code>	-j	lining (cf. <code>\lnstyle</code> above)
<code>\texto<sup>b</sup></code>	<code>\ostyle<sup>b</sup></code>	+j	oldstyle (cf. <code>\osstyle</code> above)
<code>\textp<sup>b</sup></code>	<code>\pstyle<sup>b</sup></code>	+2	proportional
<code>\textt<sup>b</sup></code>	<code>\tstyle<sup>b</sup></code>	-2	tabular
<code>\textpl<sup>c</sup></code>	<code>\plstyle<sup>c</sup></code>	-j,+2	proportional lining
<code>\textpo<sup>c</sup></code>	<code>\postyle<sup>c</sup></code>	+2j	proportional oldstyle
<code>\texttl<sup>c</sup></code>	<code>\tlstyle<sup>c</sup></code>	-j,-2	tabular lining
<code>\textto<sup>c</sup></code>	<code>\tostyle<sup>c</sup></code>	+j,-2	tabular oldstyle

<sup>a</sup> This macro is the original `nfssect` command. The result is independent of the current style of figures.

<sup>b</sup> This macro changes precisely one aspect of the current figure style. That is, the result depends on the current style of figures.

<sup>c</sup> This macro ensures a specific fully-specified figure style.

Table 5: Shape switches

Macros			
Text Command	Switch	Shape Code	Shape
–	<code>\scolshape</code>	<code>scol</code>	outline small-caps
<code>\textol</code>	<code>\olshape</code>	<code>ol</code>	outline
<code>\textsi</code>	<code>\sishape</code>	<code>si</code>	italic small-caps
<code>\textu</code>	<code>\ushape</code>	<code>u</code>	??
<code>\textscu</code>	<code>\scushape</code>	<code>su</code>	??
<code>\textui</code>	<code>\uishape</code>	<code>ui</code>	upright italic
<code>\textri</code>	<code>\rishape</code>	<code>ri</code>	reverse italic
<code>\textdf</code>	<code>\dfshape</code>	<code>n</code>	default shape
–	<code>\swstyle<sup>b</sup></code>	<code>+w,it</code>	swash family <i>and</i> shape
<code>\textsw<sup>a</sup></code>	<code>\swshape<sup>c</sup></code>		‘find a route to swash’

<sup>a</sup> Cf. `\textswash` in table 3.

<sup>b</sup> Cf. `\swashstyle` in table 3.

<sup>c</sup> Definition is kernel and option dependent, but probably doesn’t (just) change shape. See table 3 for sketch and text for details.

Table 6: Series switches: widths

Macros			
Text Command	Switch	Series Code	Width
<code>\textnw</code>	<code>\nwidth</code>	<code>+c</code>	narrow
<code>\textcd</code>	<code>\cdwidth</code>	<code>+c</code>	compact
<code>\textec</code>	<code>\ecwidth</code>	<code>+ec</code>	extra compact
<code>\textuc</code>	<code>\ucwidth</code>	<code>+uc</code>	ultra compact
–	<code>\mdwidth</code>	<code>+?m</code>	medium
<code>\textet</code>	<code>\etwidth</code>	<code>+x</code>	extended
<code>\textep</code>	<code>\epwidth</code>	<code>+x</code>	expanded
<code>\textex</code>	<code>\exwidth</code>	<code>+ex</code>	extra expanded
<code>\textux</code>	<code>\uxwidth</code>	<code>+ux</code>	ultra expanded
<code>\textrw</code>	<code>\regwidth</code>	–	regular

Table 7: Series switches: weights

Macros			
Text Command	Switch	Series Code	Weight
–	<code>\mdweight</code>	+m?	medium
<code>\textmb</code>	<code>\mbweight</code>	+mb	medium-bold
<code>\textdb</code>	<code>\dbweight</code>	+db	demi-bold
<code>\textsb</code>	<code>\sbweight</code>	+sb	semi-bold
<code>\textbd</code>	<code>\bdweight</code>	+b	bold
	<code>\bfweight</code>		
<code>\texteb</code>	<code>\ebweight</code>	+eb	extra-bold
<code>\textub</code>	<code>\ubweight</code>	+ub	ultra-bold
<code>\textlg<sup>a</sup></code>	<code>\lgweight<sup>b</sup></code>	+l	light when weight
<code>\textel</code>	<code>\elweight</code>	+el	extra-light
<code>\textul</code>	<code>\ulweight</code>	+ul	ultra-light

<sup>a</sup> Cf. `\textlt` in table 3.

<sup>b</sup> Cf. `\ltstyle` in table 3.

Package options (see section 3 may also be specified after loading either in the preamble (`compat` and `force`) or at any time (`debug`). This enables users to set options after some other package loads `nfssect-cfr` and allows additional information to be printed to the console and/or logged on local basis.

### 3 Newer L<sup>A</sup>T<sub>E</sub>X Kernels

The package tests for the presence of `\init@series@setup`. If this exists, it loads a newer version of the package. `nfssect-cfr` supports three options, but these are only effective if the newer code (for NNFSS) is loaded. All three are booleans, initially false and default to true if used without specifying a value<sup>6</sup>. The third option is described in section 5.

`force (opt.) = true|false`

Default: `true`

Initial: `false`

Scope: preamble

You can force the old code to be loaded using the package option `force` or `force=true`. Note, however, that the old version will not work as advertised on newer kernels because L<sup>A</sup>T<sub>E</sub>X will overwrite some of the package’s definitions at the end of the preamble.

<sup>6</sup>‘Default’ and ‘initial’ follow the usage in `l3interface.pdf`, `l3keys2e` and `clsguide.pdf`. If you are familiar with `pgfkeys`, the terms have the same meaning there. Basically, the ‘initial’ value is what you get if you don’t specify the option at all when loading the package, while the ‘default’ is what you get if you specify the option without specifying a value.

‘Scope’ is used in the standard sense applicable to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> class and package options. That is, it indicates whether the option may be used only when loading the package, at any point in the preamble or also in the document.

`compat` (*opt.*) = `true|false`

Default: `true`

Initial: `false`

Scope: preamble

In contrast, `compat` or `compat=true` will activate code which tries to partially replicate the original `nfssect-cfr`'s behaviour. This is far from unproblematic. In particular, it will partly break features of the current NFSS for other fonts.

If your document relies exclusively on text fonts supported by this package and none of the support for those fonts has been updated, compilation should produce a more satisfactory result than otherwise. If, however, your document relies partly on text fonts not supported by this package or the support for those fonts has been updated in the 'wrong' way, compilation may produce a less satisfactory result. There is no general rule here: whether the option helps or hinders things depends entirely on the fonts, the support for those fonts and the specific contents of your document.

The main areas known to be problematic are

1. italic small-capitals (but oblique small-capitals should be mostly unaffected);
2. swash;
3. transitions between small-caps, italic, oblique, italic small-caps, oblique small-caps, upright italic, right italic and upright;
4. any transition involving swash where shape is involved;
5. medium weight fonts where width is non-standard e.g. medium condensed, medium ultra condensed etc.;
6. medium bold weight in any context.

1–4 can be worked around at the document level, with some inconvenience. Subject to the caveats above, the `compat` option may avoid at least some of these inconveniences.

5 and 6 cannot be worked around at the document level. Nor does `nfssect-cfr` make any attempt to mitigate these two issues. Doing so would involve too much interference with current NFSS. This means that 5 and 6 can be addressed only in the support files for the fonts affected. Neither `compat` nor `force` makes any attempt to change this.

Maximum backwards compatibility requires changes to the font support files *and* `compat=false`, but some documents may still require (hopefully minor) changes.

### 3.1 Required Changes to Font Support Files

In all cases, additional changes to font substitution rules may be needed to prevent multiple substitutions by the same font, since these seem to cause problems.



**italic small-caps** The problem here is that `nfssex` encoded italic small-caps as shape `si`, whereas the kernel has plumped for `scit`. It does support `scsl` (although it does not distinguish oblique from italic), but not `si`. This issue can be more-or-less dealt with by support files for fonts, but some issues arise at the document level concerning transitions (below).

Ideally, `scit` should be substituted wherever font definition files specify the shape `si`. `scit` should then be defined as a (silent) substitution for `si`. However, it *should* be sufficient to define `si` as a substitute for `scit`.

Fonts which provide oblique small-caps, but not italic, should specify `scsl` as a (silent) substitution for `scit` and `scit` for `si` (or *vice-versa*). The kernel supports `scsl` out-of-the-box, together with the substitution for `scit`, but the changes should make support for `\textsi` and `\sishape` more robust.

**transitions** No additional changes are recommended to support files which load `nfssex-cfr`. Provided `fd` files are updated as explained above, no further adjustments should be required to enable correct font selection during transitions involving italic, oblique, small-caps, upright italic, reverse italic etc.

**swash** No changes are recommended for swash to font definition files for packages which load `nfssex-cfr`. If loading `nfssex-cfr`, the recommendation is to **ignore** the kernel's implementation because it cannot be made to work correctly with any family which provides swash for multiple shapes e.g. both upright and italic or small-caps and upper/lower case<sup>7</sup>.

**swshape** No changes for swash are recommended for `sty` files in packages which load `nfssex-cfr`.

`nfssex-cfr-nfss` contains the original `nfssex` definition of `\swshape` and `\textsw`. This is used on newer kernels only if `force` is used, in which case the code is largely broken.

`nfssex-cfr-nfss` contains both the original definition and a replacement. The former is used only if `compat` is selected; otherwise, the latter is used on kernels supporting `NNFSS`. The new definition tries to figure out which of the three possible implementations, if any, to use and behaves accordingly. **The kernel definition is overwritten regardless.** `compat` determines only *what* overwrites the kernel's.

**medium** Any line of a font definition file which codes a series of two or more letters including `m` must be changed to delete the `m`. For example, `{mc}` → `{c}`, `{muc}` → `{uc}` etc. **It is NOT sufficient to substitute such series using rules.** The changes **must** be made in the primary definitions of the font families.

<sup>7</sup>The issue here is that the kernel considers swash to be a *shape*, whereas `nfssex` only *called* it a shape. The underlying code treated it as a *style* requiring a change of font *family*. The shape was always (potentially switched to) italic (`it`). `nfssex-cfr` offered a second version of swash, which treats it as a family possibly requiring a change of shape, but the shape is typically italic or upright, as opposed to being specific to swash.

To make things worse, not all fonts *can* be setup in the way the kernel assumes because some fonts provide swash characters in a variety of shapes (upright and italic, for example). Moreover, it is common to encode additional ligatures, for example, as swash, even though this is not accurate, in order to provide *some* mechanism for accessing them within a traditional 8-bit font setup.

**mb** I've chosen to make `\mbweight` an alias for `\sbweight`. Hopefully no font family supports both. Provided that's not the case, **mb** should be changed to `\sb` in all affected font definition files. **It is NOT sufficient to substitute `mb` for `sb` using a rule.** The change **must** be made in the definition of the family.

## 4 Older L<sup>A</sup>T<sub>E</sub>X Kernels

This is the code base `nfssect` was written for. `nfssect-cfr` extended that code.

To the best of my knowledge, the code used with older L<sup>A</sup>T<sub>E</sub>X kernels works as expected. This means it is fully compatible with the Font Installation Guide and that things like `\scshape` `\itshape` will produce italic small-caps, as expected. This code is also — again to the best of my knowledge — fully compatible with all features of NFSS with the single exception of code supporting medium weight, condensed width fonts which erroneously uses `mc` rather than `c`.

Italic small-caps is assumed to be coded as `si`. Oblique small-caps is assumed to be coded as `scl`.

If a set of fonts provides a swash *family*, it is assumed the fonts are named in accordance with the Berry scheme. `\textswash`, `\swshape`, `\swashstyle` and/or `\swstyle` can then be used to access this family.

The difference between `\swashstyle` and `\swstyle` is that the former tries to merge any swash family with the current one, whereas the latter does not. So, if a font set provides swash for two widths of font, say, and you've changed widths, `\swashstyle` will try to find a swash character without altering the width, whereas `\swstyle` will first switch to the base font, resetting the width. On the other hand, if the font only provides swash in the standard width, say, and you've changed widths, `\swashstyle` will fail to switch to swash, whereas `\swstyle` will succeed. Packages which include swash families should, therefore, advise users which command(s) to use.

`\textswash` is the text font command for `\swashstyle`. `\textsw` is the text font command for `\swshape`.

`\swshape` first tries `\swstyle` before changing the shape to `\swshapedefault`. By default, this is `\itdefault` because swash families are often coded as italic, but this is obviously font-dependant.

## 5 Bugs, Non-Bugs & Debugging

The actual effect of any macro depends on any changes made to the defaults for various font features, the current font and, of course, what is available.

The macros operating on family names are almost entirely reliant on font names adhering strictly to the Karl Berry schema. This includes the stipulation that multiple variants be listed in alphabetical order. These macros cannot be used with fonts named in any other way.

On older kernels (NFSS), changes to weight and width should work and most shapes should be supported, but italic small-caps is assumed to be coded as `si` on these kernels, so you may need something like

```
\renewcommand*{\sdefault}{scit}% or scsl or whatever
```

On newer kernels, italic small-caps should be encoded as explained above and `\sishape/\textsi` should work out-of-the-box with packages which use any of `si`, `scit` or `scsl`.

If a macro's attempt to enable or disable a font feature fails, a warning will generally be written to the console, but the code tries hard not to trigger errors. If an attempt triggers an error, that's a bug, so please let me know. If an attempt triggers a warning, please note that there may be no bug at all and, if there is a bug, it is probably not in this package<sup>8</sup>

```
debug (opt.) = true|false
```

Default: `true`

Initial: `false`

Scope: `general`

You can get a bit more information printed to the console about what's happening using this option on newer kernels. Some of the same information can also be found in the log.

## 6 Implementation

You do not need to read the remainder of this document in order to install or use the package.

### 6.1 Main package file

This used to be the complete package. Now it is mostly responsible for processing options, figuring out which kernel we're on and implementing the small amount of code shared between the implementations for NFSS and NNFSS.

```
nfssext-cfr (pkg.)
```

```
1 \NeedsTeXFormat{LaTeX2e}
2 \RequirePackage{svn-prov}
3 \ProvidesPackageSVN[\filebase.sty]{\Id: nfssext-cfr.dtx 11042 2025-06-22
  22:34:34Z cfrees $}[v1.3 \revinfo{} extensions for NFSS and NNFSS; based
  on 2003/03/14 v1.2 Experimental NFSS Extensions]
4 \DefineFileInfoSVN
```

---

<sup>8</sup>To be clear, there certainly are bugs. It is just statistically unlikely that any given warning is caused by one.

```
\if@nfssectcfr@digonnew
```

```
5 \newif\if@nfssectcfr@digonnew
6 \@nfssectcfr@digonnewtrue
```

Copied verbatim, excepting format and modulo package/module name from Joseph Wright's `siunitx.sty` under LPPL

```
7 \@ifundefined{ExplLoaderFileDate}{%
8 \IfFileExists{expl3.sty}{%
9 \RequirePackage{expl3}%
10 }{%
11 \RequirePackage{nfssect-cfr-nfss}%
12 \@nfssectcfr@digonnewfalse
13 }%
14 }{}
15 \if@nfssectcfr@digonnew
```

Almost verbatim from `siunitx.sty`

```
16 \@ifl@t@r\ExplLoaderFileDate{2022-02-24}{%
17 }{%
18 \RequirePackage{nfssect-cfr-nfss}%
19 \@nfssectcfr@digonnewfalse
20 }%
21 \fi
22 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
23 \if@nfssectcfr@digonnew
```

BEGIN expl pkg option setup

```
24 \newif\ifexfs@debug
25 \ExplSyntaxOn
26 \prop_gput:Nnn \g_msg_module_name_prop { nfssect-cfr } { exfs }
27 \bool_new:N \l__exfs_tmpa_bool
28 \keys_define:nn { exfs }
29 {
```

`compat` (*opt.*) Compatibility option.

```
\g__exfs_compat_bool
30 compat .bool_gset:N = \g__exfs_compat_bool,
31 compat .default:n = true,
32 compat .initial:n = false,
33 compat .usage:n = preamble,
```

`debug` (*opt.*) Turns info messages into warnings for testing purposes and possibly provides additional information.

```
34 debug .legacy_if_gset:n = exfs@debug,
35 debug .initial:n = false,
36 debug .default:n = true,
```

`force` (*opt.*) Force loading of code for NFSS even on newer kernels.

```
\g__exfs_force_bool
```

```

37   force .bool_gset:N = \g__exfs_force_bool,
38   force .default:n = true,
39   force .initial:n = false,
40   force .usage:n = preamble,
41 }

```

Joseph Wright: from siunitx.sty ; <https://chat.stackexchange.com/transcript/message/64327823#64327823>

```

42 \providecommand \IfFormatAtLeastTF { \@ifl@t@r \fmtversion }
43 \IfFormatAtLeastTF { 2022-06-01 }
44 {
45   \ProcessKeyOptions [ exfs ]
46 }{
47   \RequirePackage { l3keys2e }
48   \ProcessKeysOptions { exfs }

```

\ProcessKeyOptions

```

49   \NewDocumentCommand \ProcessKeyOptions { o }
50   {
51     \IfValueTF { #1 } { \ProcessKeysOptions { #1 } }
52     { \PackageError{nfssect-cfr}{
53       Optional-argument-mandatory-on-kernels-this-old.\MessageBreak
54       Please-specify-the-module-whose-keys-should-be-processed
55     }{
56       \protect\ProcessKeyOptions-only-passes-keys-to~
57       \protect\ProcessKeyOptions\MessageBreak
58       on-older-kernels-for-the-convenience-of-package-authors.-
59       Since-\protect\ProcessKeysOptions\MessageBreak
60       takes-an-argument,~the-optional-argument-to~
61       \protect\ProcessKeyOptions-is-required
62     }
63   }
64 }
65 }
66 \IfFormatAtLeastTF { 2020-10-01 }{
67 }{
68   \RequirePackage { xparse }

```

\ExpandArgs

```

69   \providecommand \ExpandArgs [1]
70   { \cs_if_exist_use:c { exp_args:N #1 } }
71 }

```

END expl pkg option setup

BEGIN cfr-added: bifurcate

We test for the presence of `\init@series@setup` in order to determine whether to load code for NNFSS or NFSS. If `force` is set, we load for NFSS regardless.

```

72 \RequirePackage{etoolbox}
73 \msg_new:nnn { nfssect-cfr } { compat }
74 {
75   You ~ or ~ a ~ font-support ~ package ~ have ~ loaded ~ me ~ ( line ~
\msg_line_number: ) ~ with ~ the ~ compat ~ option. ~
76   This ~ means ~ the ~ package ~ may ~ require ~ updating. ~
77   Update ~ the ~ package ~ if ~ necessary ~ and ~ use ~ compat=false ~
when ~ loading ~ me.
78 }
79 \msg_new:nnn { nfssect-cfr } { force }
80 {
81   You ~ or ~ a ~ font-support ~ package ~ have ~ loaded ~ me ~ ( line ~
\msg_line_number: ) ~ with ~ the ~ force ~ option. ~
82   This ~ is ~ a ~ desperate ~ measure ~ of ~ last ~ resort. ~
83   **Breakage ~ is ~ expected.**
84 }
85 \hook_gput_code:nnn { begindocument/before } { . }
86 {
87   \cs_if_exist:NTF \init@series@setup
88   {
89     \bool_if:NTF \g__exfs_force_bool
90     {
91       \msg_warning:nn { nfssect-cfr } { force }
92       \RequirePackage {nfssect-cfr-nfss}
93     }{
94       \bool_if:NT \g__exfs_compat_bool
95       {
96         \msg_warning:nn { nfssect-cfr } { compat }
97       }
98       \RequirePackage {nfssect-cfr-nfss}
99     }
100   }{% achosiad heb broblemiau - diolch byth!
101     \RequirePackage {nfssect-cfr-nfss}
102   }
103 }

```

This code is here to enable backwards-compatible encoding declarations in font definition files. We have three cases: (1) the format predates NNFSS, in which case the commands probably don't exist at all, (2) the format is recent enough for NNFSS but predates the November 2024 'hotfix' release (2024-11-19), in which case the commands will return errors after the preamble and (3) the format is at least as new as the 'hotfix', in which case the macros' definitions should be fine. This requires we check whether *both* the format is no older than 2024-11-01 *and* the patch level is at least 1<sup>9</sup>.

In this third case, we do nothing.

```

104 \bool_set_false:N \l__exfs_tmpa_bool
105 \IfFormatAtLeastT { 2024-11-01 }
106 {
107   \ifnum\patch@level>0
108     \bool_set_true:N \l__exfs_tmpa_bool

```

<sup>9</sup>At least, it seems to, though it also seems there ought to be a more straightforward way to check what is essentially the release date or version?

```

109   \fi
110   }
111   \bool_if:NF \l__exfs_tmpa_bool
112   {
113     \cs_if_free:NTF \DeclareEncodingSubset
114     {

```

`\DeclareEncodingSubset` If the macro isn't even defined in the preamble, define it to absorb three arguments.

```

115     \def\DeclareEncodingSubset#1#2#3{
116     }{

```

`\@DeclareEncodingSubset@copi` Otherwise, we save the preamble definition of the innermost definition on 'in between' kernels.

```

117     \let\@DeclareEncodingSubset@copi\@DeclareEncodingSubset
118     \hook_gput_code:nnn { begindocument / end } { . }
119     {

```

Simpler than the kernel version because we're only interested in use inside `fd` files. If the declarations are in `sty` files, it doesn't matter what definitions are in place inside the document environment.

**Note the syntax differs from the kernel/preamble version.** The macro expects three arguments, but the star syntax is **not** supported as it makes no sense in font definition files, which are family-specific.

```

120     \let\DeclareEncodingSubset\@DeclareEncodingSubset@copi
121     \PackageWarning{nfssect-cfr}{Overwriting ~ the ~ format's ~ definition
~ of ~ \string\DeclareEncodingSubset{ } }
122   }
123   }
124   }

```

`\__exfs_set:n`

```

125   \cs_new_protected_nopar:Nn \__exfs_set:n
126   {
127     \keys_set:nn { exfs } { #1 }
128   }

```

`\nfssectset` Allow setting of options later in preamble or in document. This is intended to enable debugging to be toggled locally.

```

129   \cs_set_eq:NN \nfssectset \__exfs_set:n
130   \ExplSyntaxOff

```

END added

`\DeclareTextOrnament` These are unmodified from `nfssect`. I'm not aware of any [CTAN](#) packages using `\ornament` these and they have not been tested for compatibility with `NNFSS`, though I can't see any patently obvious problems.

```

131 \newcommand*\DeclareTextOrnament}[7]{%
132   \expandafter\def\csname#1@orn@\roman#2\endcsname{#3/#4/#5/#6/#7}}
133 \begingroup
134   \catcode'\/=12
135   \gdef\exfs@split@orndef#1/#2/#3/#4/#5\@nil{%
136     \def\f@encoding{#1}%
137     \def\f@family{#2}%
138     \def\f@series{#3}%
139     \def\f@shape{#4}%
140     \def\exfs@tempa{#5}}
141 \endgroup
142 \def\exfs@base@family{\expandafter\exfs@get@base\f@family\@nil}
143 \DeclareRobustCommand{\ornament}[1]{%
144   \expandafter\ifx\csname\exfs@base@family @orn@\roman#1\endcsname\relax
145     \PackageWarning{nfssect}{%
146       Ornament #1 undefined for font family '\exfs@base@family'\MessageBreak
147       Setting debug mark}%
148     \rule{1ex}{1ex}%
149   \else
150     \begingroup
151       \edef\exfs@tempb{\csname\exfs@base@family @orn@\roman#1\endcsname}%
152       \expandafter\expandafter\expandafter\exfs@split@orndef
153       \expandafter\string\exfs@tempb\@nil
154       \selectfont\char\exfs@tempa
155     \endgroup
156   \fi}

```

\nfssectcfr@MT@Hook BEGIN add microtype hooks Partly from microtype docs; partly from MinionPro  
 \Microtype@Hook package

```

157 \def\nfssectcfr@MT@Hook{%
158   \DeclareMicrotypeVariants*{2,2d,2dj,2j,dj,e,h,l}% is this necessary or
      would the previous line be enough?
159 }
160 \@ifpackageloaded{microtype}{%
161   \PackageWarning{nfssect-cfr}{%
162     You have loaded me (or a font support package which loads me)\MessageBreak
163     after loading microtype, but microtype should be loaded after\MessageBreak
164     all font defaults have been setup}%
165   \nfssectcfr@MT@Hook
166 }{%
167   \@ifundefined{Microtype@Hook}{%
168     \let\Microtype@Hook\nfssectcfr@MT@Hook
169   }{% MinionPro has \global before this
170     \g@addto@macro\Microtype@Hook{\nfssectcfr@MT@Hook}%
171   }%
172 }

173 \fi
174 % END

```



## 6.2 NNFSS

This code was written for the *current* (New) New Font Selection Scheme (2020–). It should not generally be loaded on older kernels.

`nfssect-cfr-nfss` (*pkg.*)

```

175 \NeedsTeXFormat{LaTeX2e}
176 \RequirePackage{svn-prov}
177 \ProvidesPackageSVN[\filebase-nfss.sty]{\Id: nfssect-cfr.dtx 11042 2025-06-22
    22:34:34Z cfrees $}[v1.3 \revinfo{ } extended New New Font Selection Scheme
    (NNFSS) based on 2003/03/14 v1.2 Experimental NFSS Extensions]
178 \DefineFileInfoSVN

```

END added

`\exfs@tempa` Scratch variables.

`\exfs@tempb`

```
179 \newcommand*{\exfs@tempa}{}

```

```
180 \newcommand*{\exfs@tempb}{}

```

:end-added BEGIN added (cfr): extra variable (`\exfs@tempf`)

```
181 \newcommand*{\exfs@tempf}{}

```

We want to track cases where missing fonts get defined into existence. To do this we define an additional macro each time `\wrong@fontshape` is called. This is based on two proposals by Max Chernoff, but the implementation is different.

```

182 \ExplSyntaxOn
183 \hook_gput_code:nnn { cmd/wrong@fontshape/before } { . }
184 {
185   \global\expandafter\expandafter\expandafter\let
186   \expandafter \csname exfs@fake@ \curr@fontshape\endcsname\relax
187 }
188 \ExplSyntaxOff

```

`\exfs@info` Custom logging

```

189 \newcommand \exfs@info[2] [nfssect-cfr]{%
190   \ifexfs@debug
191     \PackageWarning{#1}{Info: #2}%
192   \else
193     \PackageInfo{#1}{#2}%
194   \fi
195 }

```

END added

`\exfs@normalise` BEGIN added (cfr): normalise

```

196 \newcommand* \exfs@normalise[1]{%
197   \ifcsname exfs@fake@\curr@fontshape\endcsname
198     \exfs@info{Current font '\curr@fontshape' is fake.\MessageBreak
199       Normalising}%

```

```

200 \expandafter\csname f@#1\endcsname{\csname #1default\endcsname}\selectfont
201 \ifcsname exfs@fake@\curr@fontshape\endcsname
202 \f@series{\seriesdefault}\f@shape{\shapedefault}\selectfont
203 \ifcsname exfs@fake@\curr@fontshape\endcsname

```

This might happen, I think, if we're in a swash family or specialist encoding where the default series and shape aren't available. All bets are off here so try to bale out as gracefully as we can.

```

204 \normalfont
205 \ifcsname exfs@fake@\curr@fontshape\endcsname

```

This definitely oughtn't to happen, though - things are really screwed up at this point - so error.

```

206 \PackageError{nfssect-cfr}{Default font appears to be fake!\MessageBreak
207 Switch \textbackslash normalfont yielded '\curr@fontshape'}
208 {This is highly unlikely, so the bug is probably in the phenomena\MessageBreak
209 rather than the noumena}%
210 \fi
211 \fi
212 \fi
213 \exfs@info{Normalised to '\curr@fontshape'}%
214 \else
215 \exfs@info{Current font '\curr@fontshape' appears real}%
216 \fi
217 }

```

END added

`\exfs@try@family` Modified from `nfssect`? Or modified from older `nfssect-cfr`?

```

218 \newcommand*{\exfs@try@family}[2][]{%
219 \let\exfs@tempa\relax

```

END added

trans: group is requisite here else L<sup>A</sup>T<sub>E</sub>X thinks the family real regardless

```

220 \begingroup % fel arall, bydd latex yn credu bod y family yn go iawn beth
      bynnag

```

(o leiaf bydd latex yn dweud felly)

```

221 \exfs@info{Trying Font family '\f@encoding/#2'}%
222 \fontfamily{#2}\try@load@fontshape

```

`\curr@fontshape` holds the target shape - not the current one - after an unsuccessful attempt to load **family** with `\try@load@fontshape`. This won't work for series/shape as `\curr@fontshape` holds the current one in that case

```

223 \expandafter\ifx\csname\curr@fontshape\endcsname\relax
224 \edef\exfs@tempa{#1}%
225 \ifx\exfs@tempa\@empty
226 \PackageWarning{nfssect}{%
227 Font family '\f@encoding/#2' not available\MessageBreak
228 Ignoring font switch}%

```

```

229     \else
230     \exfs@info[nfssect]{%
231         Font family '\f@encoding/#2' not available\MessageBreak
232         Font family '\f@encoding/#1' tried instead}%
233     \exfs@try@family{#1}%
234     \fi
235     \else
236     \exfs@info{Loading font family '\f@encoding/#2'}%
237     \gdef\exfs@tempa{\fontfamily{#2}\selectfont}%
238     \fi
239 \endgroup
240 \exfs@tempa}

```

`\exfs@try@series` BEGIN added (cfr)

```
241 \newcommand*{\exfs@try@series}[2] []{%
```

We don't hand instructions to the kernel unless we know they'll succeed b/c the results are too unpredictable under NNFSS.

Changing directly only produces usable results for series defined in the 'table' of font changes. But using higher level kernel interfaces for tests doesn't work because spurious fonts get defined, which only seem to exist. Theoretically, we might as well use the existing kernel's macros since we're already damned by reliance on internals anyway. But then everything needs disentangling. So it's easier to just adapt previous tests, even though it partially duplicates what the kernel does. (But it isn't the mess swash is ...).

```

242 \let\exfs@targetseries\relax
243 \edef\exfs@tempa{#2}%
244 \ifx\f@series\exfs@tempa\relax
245 \exfs@info{Current (\f@series) matches target (#2) series.\MessageBreak
246 Ignoring font switch}%
247 \else
248 \begingroup
249 \exfs@normalise{series}%
250 \edef\exfs@tempa{\f@encoding/\f@family/#2/\f@shape}%
251 \ifcsname \exfs@tempa\endcsname
252 \exfs@info{Switching series: \f@series\space -> #2}%
253 \gdef\exfs@targetseries{\fontseries{#2}\selectfont}%
254 \else
255 \edef\exfs@reserved{#1}%
256 \ifx\exfs@reserved\@empty
257 \PackageWarning{nfssect-cfr}{%
258 Font series '\f@encoding/\f@family/#2/\f@shape' not available\MessageBreak
259 Ignoring font change}%
260 \else
261 \PackageWarning{nfssect-cfr}{%
262 Font series '\f@encoding/\f@family/#2/\f@shape' not available\MessageBreak
263 Trying '\f@encoding/\f@family/#1/\f@shape'}%
264 \exfs@try@series{#1}%
265 \fi
266 \fi
267 \endgroup
268 \exfs@targetseries

```

```
269 \fi}
```

`\exfs@try@shapeshift` Attempt to leverage kernel's mechanism.

```
270 \def\exfs@try@shapeshift#1{%
271 \edef\exfs@targetshape{\csname #1default\endcsname}%
272 \ifx\f@shape\exfs@targetshape\relax
273 \exfs@info{Current (\f@shape) matches target (#1) shape.\MessageBreak
274 Ignoring font switch}%
275 \else
276 \not@math@alphabet\edef\exfs@targetshape\relax
277 \exfs@info{\f@shape\space -> \exfs@targetshape\MessageBreak
278 Trying \f@encoding/\f@family/\f@series/\exfs@targetshape}%
```

We *do* want the kernel's substitution mechanism here?

```
279 \fontshape{\exfs@targetshape}\selectfont
280 \fi}
```

`\exfs@swshape` Switching to swash is now far more complicated with (I presume) the attendant overhead, but the kernel's approach just won't work here<sup>10</sup>. This will become `\swshape` if `compat` isn't enabled.

```
281 \newcommand* \exfs@swshape{%
282 \let\exfs@targetsw\relax
283 \begingroup % angen neu beidio? angen - bendant!
```

Try kernel or configured default first so we get swash from current family etc. if available

```
284 \edef\exfs@tempa{\f@encoding/\f@family/\f@series/\swdefault}%
285 \edef\exfs@tempa@fake{\exfs@fake\exfs@tempa}%
286 \ifcsname \exfs@tempa\endcsname
287 \ifcsname \exfs@tempa@fake\endcsname
288 \exfs@swfamily
289 \else
290 \gdef\exfs@targetsw{\fontshape{\swdefault}\selectfont}% kernel
291 \fi
292 \else
293 \exfs@swfamily
294 \fi
295 \endgroup
296 \ifx\exfs@targetsw\relax
297 \PackageWarning{nfssext-cfr}{%
298 Cannot find any route to swash.\MessageBreak
299 Are you sure one is available?}%
300 \else
301 \exfs@targetsw
302 \exfs@info{Switch to swash resulted in '\curr@fontshape'}%
```

<sup>10</sup>Implementing swash as a *shape* isn't workable for fonts I've packaged, so I've made no attempt to follow the kernel here as I do for small-caps italic etc. We're back to the single axis/multiple aspect problem which NNFSS created by ignoring small-caps/italic and width/weight combinations. It may, in fact, be wrong-headed to follow the kernel *at all* here. Perhaps it would be better to just provide the original implementation and some compatibility option for people who also need swash shapes in the same document?

```

303 \fi
304 }

```

`\exfs@swfamily` This is the guts of `\exfs@swshape`.

```

305 \newcommand* \exfs@swfamily{%
306 \let\exfs@targetsw\relax
307 \begingroup

```

Try `nfssex-cfr` family switch & our default or configured

```

308 \let\exfs@tempa\f@family
309 \exfs@merge@families{w}%
310 \ifx\exfs@tempa\f@family % try merge with current shape

```

Try switching to upright etc. first

```

311 \fontshape{n}%
312 \exfs@merge@families{w}% up & merge
313 \if\exfs@tempa\f@family

```

Try switching to `\swshapedefault` first

```

314 \fontshape\swshapedefault
315 \exfs@merge@families{w}% up & nfssex-cfr default/configured
316 \if\exfs@tempa\f@family

```

Use `nfssex` family switch & default or configured

```

317 \exf@try@family{\expandafter\exfs@get@base\f@family@nil w}% nfssex
switch
318 \if\exfs@tempa\f@family % nfssex switch
319 \fontshape\swshapedefault\exfs@try@family{%
320 \expandafter\exfs@get@base\f@family@nil w}% nfssex switch &
shape
321 \if\exfs@tempa\f@family
322 \relax % rhodd y ffidl yn y to (give up)
323 \else
324 \gdef\exfs@targetsw{%
325 \fontshape\swshapedefault\expandafter\fontfamily{%
326 \exfs@get@base\f@family@nil w}\selectfont
327 }% nfssex switch & shape
328 \fi % nfssex switch & shape
329 \else
330 \gdef\exfs@targetsw{\expandafter\fontfamily{%
331 \exfs@get@base\f@family@nil w}\selectfont
332 }% nfssex switch
333 \fi % nfssex switch
334 \else
335 \gdef\exfs@targetsw{%
336 \fontshape\swshapedefault\exfs@merge@families{w}%
337 }% up & nfssex-cfr default/configured
338 \fi % up & nfssex-cfr default/configured
339 \else
340 \gdef\exfs@targetsw{%
341 \fontshape{n}\exfs@merge@families{w}%

```

```

342     }% up & merge
343     \fi % up & merge
344     \else
345     \gdef\exfs@targetsw{\exfs@merge@families{w}}% merge with current shape
346     \fi % merge with current shape
347 \endgroup
348 }

```

END added

\exfs@get@base Utilities

```

\exfs@get@variants
  \exfs@next 349 \def\exfs@get@base#1#2#3#4\@nil{#1#2#3}
  \exfs@shift BEGIN added (cfr): more \exfs@ commands (get@variants, next, shift, first,
  \exfs@first part, second)
  \exfs@part
  \exfs@second 350 \def\exfs@get@variants#1#2#3#4\@nil{#4}
351 \def\exfs@next#1#2\@nil{#1}
352 \def\exfs@shift#1#2\@nil{#2}
353 \def\exfs@first#1#2\@nil{#1}
354 \def\exfs@part#1#2\@nil{#2}
355 \def\exfs@second#1#2#3\@nil{#2}

```

\exfs@series@splitter Common method for dealing with weight and width.

```

356 \def\exfs@series@splitter#1{%
357   \edef\exfs@weight{\expandafter\exfs@first#1\@nil}%
358   \edef\exfs@width{\expandafter\exfs@shift#1\@nil}%

```

Two char width only or two char weight

```

359   \if\exfs@weight u\exfs@check@cx{u}%
360   \else\if\exfs@weight e\exfs@check@cx{e}%
361   \else\if\exfs@weight s\exfs@check@cx{s}%
362   \else\if\exfs@weight d\exfs@check@cx{d}%
363   \else\ifx\exfs@width\@empty % m dealt with elsewhere

```

Single character width

```

364   \if\exfs@weight c\def\exfs@width{c}\let\exfs@weight\@empty
365   \else\if\exfs@weight x\def\exfs@width{x}\let\exfs@weight\@empty
366   \fi\fi
367 \fi\fi\fi\fi\fi
368 \exfs@info{#1 -> \exfs@weight:\exfs@width;}%
369 }

```

\exfs@check@cx Auxiliary for \exfs@check@cx

```

370 \def\exfs@check@cx#1{%
371   \edef\exfs@tempa{\expandafter\exfs@first\exfs@width\@nil}%
372   \if\exfs@tempa c\edef\exfs@width{#1c}\let\exfs@weight\@empty
373   \else\if\exfs@tempa x\edef\exfs@width{#1x}\let\exfs@weight\@empty
374   \else\edef\exfs@weighta{%
375     \exfs@weight\exfs@tempa

```

```

376     }\let\exfs@weight\exfs@weighta
377     \edef\exfs@widtha{%
378         \expandafter\exfs@shift\exfs@width\@nil
379     }\let\exfs@width\exfs@widtha
380 \fi\fi
381 }

```

END added

```

\lnstyle Unmodified from nfssect. Anniffiniedig -> undefined in the kernel.
\osstyle
\infstyle 382 \DeclareRobustCommand{\lnstyle}{%% anniffiniedig
\instyle 383 \not@math@alphabet\lnstyle\relax
\instyle 384 \exfs@try@family[\expandafter\exfs@get@base\f@family\@nil]%
\sustyle 385     {\expandafter\exfs@get@base\f@family\@nil x}}
\swstyle 386 \DeclareRobustCommand{\osstyle}{%% anniffiniedig
387 \not@math@alphabet\osstyle\relax
388 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil j}}
389 \DeclareRobustCommand{\instyle}{%% anniffiniedig
390 \not@math@alphabet\instyle\relax
391 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil 0}}
392 \let\infstyle\instyle
393 \DeclareRobustCommand{\sustyle}{%% anniffiniedig
394 \not@math@alphabet\sustyle\relax
395 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil 1}}
396 \DeclareRobustCommand{\swstyle}{%% anniffiniedig
397 \not@math@alphabet\swstyle\relax
398 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil w}}

```

BEGIN added (cfr) - merge families.

NNFSS (unsurprisingly) does nothing here, so this is unproblematic. The following depends **absolutely** on **complete** adherence to berry names.

`\ifexfs@added \exfs@merge@families` is used in the macros recommended for switching the style of figures, activating swash and other variants etc.

```

399 \newif\ifexfs@added
400 \newcommand*\exfs@merge@families[1]{%
401 \edef\exfs@vartomerge{#1}%
402 \edef\exfs@variants{\expandafter\exfs@get@variants\f@family\@nil}%
403 \exfs@info{Trying to merge variants #1 and \exfs@variants}%
404 \edef\tempo{2j}%
405 \let\exfs@tempq\@empty
406 \def\exfs@tempg{}%
407 \exfs@addedfalse

```

Check whether there are variants - if not just use the requested addition.

```

408 \ifx\exfs@variants\@empty
409 \edef\exfs@tempq{\exfs@vartomerge}%
410 \exfs@addedtrue
411 \else
412 \gdef\set{0,1,2,a,d,e,f,h,j,l,p,q,s,t,v,w}% these are the variants to
consider - the order here and in the font name is crucial

```

```

413     \ifx\tempo\exfs@vartomerge
414     \@for \xx:=\set \do {%

```

Check whether there are variants left - if not set the ‘next variant’ to empty

```

415         \ifx\exfs@variants\@empty
416         \let\exfs@nextvariant\@empty
417         \else

```

O/w get the next variant

```

418             \edef\exfs@nextvariant{\expandafter\exfs@next\exfs@variants\@nil}%
419             \fi

```

If the next variant is 2 or j, ignore it

```

420         \if\exfs@nextvariant 2%
421         \edef\exfs@variants{\expandafter\exfs@shift\exfs@variants\@nil}%
422         \fi
423         \if\exfs@nextvariant j% if the next variant is j, ignore it
424         \edef\exfs@variants{\expandafter\exfs@shift\exfs@variants\@nil}%
425         \fi

```

See if the current value is either 2 or j and add it if so and if needed

```

426         \if\xx 2%
427         \edef\exfs@tempg{\exfs@tempg\xx}%
428         \else
429         \if\xx j% if the current value is j, we’re done
430         \edef\exfs@tempq{\exfs@tempg\xx\exfs@variants}%
431         \let\exfs@variants\@empty
432         \exfs@addedtrue
433         \else

```

o/w see if the current value matches the next variant

```

434             \ifx\xx\exfs@nextvariant
435             \edef\exfs@tempg{\exfs@tempg\xx}%
436             \edef\exfs@variants{\expandafter\exfs@shift\exfs@variants\@nil}%
437             \fi
438         \fi
439     \fi
440 }%
441 \else
442     \@for \xx:=\set \do {%

```

Check whether there are variants left and, if not, add the addition if needed

```

443         \ifx\exfs@variants\@empty
444         \ifexfs@added
445         \else
446         \edef\exfs@tempq{\exfs@tempg\exfs@vartomerge}%
447         \exfs@addedtrue
448         \fi
449         \else

```

o/w get the next variant



```
450         \edef\exfs@nextvariant{\expandafter\exfs@next\exfs@variants\@nil}%
```

If the new token equals the next variant, combine whatever is saved in `\exfs@tempg` with whatever remains in `\exfs@variants`

```
451         \ifx\exfs@nextvariant\exfs@vartomerge
452             \edef\exfs@tempq{\exfs@tempg\exfs@variants}%
453             \exfs@addedtrue
454             \let\exfs@variants\@empty
455         \else
```

o/w, if the current value matches the requested addition, add it in

```
456             \ifx\exfs@vartomerge\xx
457                 \edef\exfs@tempq{\exfs@tempg\xx\exfs@variants}%
458                 \exfs@addedtrue
459                 \let\exfs@variants\@empty
460             \else
```

o/w, if the current value matches the next variant, shift

```
461                 \ifx\exfs@nextvariant\xx
462                     \edef\exfs@tempg{\exfs@tempg\xx}%
463                     \edef\exfs@variants{\expandafter\exfs@shift\exfs@variants\@nil}%
464                 \fi
465             \fi
466         \fi
467     \fi
468 }%
469 \fi
470 \fi
471 \ifx\exfs@tempq\@empty
472     \PackageError{nfssect-cfr}{Something is wrong here. Ignoring font switching
command.}{}%
473 \else
474     \exfs@try@family{\expandafter\exfs@get@base\family\@nil \exfs@tempq}%
475 \fi
476 }
```

`\pstyle` Commands for switching to proportional and/or oldstyle figures. Compare `\ostyle` `\ostyle` with `nfssect`'s `\osstyle` above. These macros (and the block which follows) all `\postyle` require merging Berry names but not unmerging.

```
477 \DeclareRobustCommand{\pstyle}{%% anniffiniedig proportional figures
478     \not@math@alphabet\pstyle\relax
479     \exfs@merge@families{2}}
480 \DeclareRobustCommand{\ostyle}{%% anniffiniedig oldstyle figures (cf. original
ostyle above)
481     \not@math@alphabet\ostyle\relax
482     \exfs@merge@families{j}}
```

Combined command for proportional oldstyle

```
483 \DeclareRobustCommand{\postyle}{%% anniffiniedig
484     \not@math@alphabet\postyle\relax
485     \exfs@merge@families{2j}}
```

```

\tistyle These macros again require merging, but not unmerging, names.
\ltstyle
\ofstyle 486 \DeclareRobustCommand{\tistyle}{%% anniffiniedig titling/display
\altstyle 487 \not@math@alphabet\tistyle\relax
\regstyle 488 \exfs@merge@families{d}}
\embossstyle Note that this command is for use when the light version is a separate family rather
\ornamentalstyle than a weight variant (e.g. when you've got light, light bold etc. as well as regular
\swashstyle weights)
\shstyle
\qtstyle 489 \DeclareRobustCommand{\ltstyle}{%% anniffiniedig
490 \not@math@alphabet\ltstyle\relax
491 \exfs@merge@families{l}}

```

Let's hope there aren't any fonts with a light family *\*and\** an outline/openface/blank version

```

492 \DeclareRobustCommand{\ofstyle}{%% anniffiniedig
493 \not@math@alphabet\ofstyle\relax
494 \exfs@merge@families{l}}
495 \DeclareRobustCommand{\altstyle}{%% anniffiniedig alternative style
496 \not@math@alphabet\altstyle\relax
497 \exfs@merge@families{a}}
498 \DeclareRobustCommand{\regstyle}{%% anniffiniedig 'regular' style
499 \not@math@alphabet\regstyle\relax
500 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil}}
501 \DeclareRobustCommand{\embossstyle}{%% anniffiniedig
502 \not@math@alphabet\embossstyle\relax
503 \exfs@merge@families{e}}
504 \DeclareRobustCommand{\ornamentalstyle}{%% anniffiniedig intended primarily
for decorative initial fonts etc.
505 \not@math@alphabet\ornamentalstyle\relax
506 \exfs@merge@families{p}}
507 \DeclareRobustCommand{\qtstyle}{%% anniffiniedig quotation style (assumes
sans)
508 \not@math@alphabet\qtstyle\relax
509 \sffamily
510 \exfs@merge@families{q}}
511 \DeclareRobustCommand{\shstyle}{%% anniffiniedig
512 \not@math@alphabet\shstyle\relax
513 \exfs@merge@families{h}}
514 \DeclareRobustCommand{\swashstyle}{%% anniffiniedig an attempt to improve
on \swstyle
515 \not@math@alphabet\swashstyle\relax
516 \exfs@merge@families{w}}

```

`\tmstyle` Macros to switch between monowidth and variable typewriter. These need to  
`\tvstyle` unmerge before merging. We need to unmerge sans as well as the other kind of  
typewriter.

```

517 \DeclareRobustCommand{\tmstyle}{%% anniffiniedig monowidth typewriter
518 \not@math@alphabet\tmstyle\relax
519 \exfs@unmerge@families{s}%
520 \exfs@unmerge@families{v}%
521 \exfs@merge@families{t}}

```

```

522 \DeclareRobustCommand{\tvstyle}{% anniffiniedig      variable width typewriter
523   \not@math@alphabet\tvstyle\relax
524   \exfs@unmerge@families{s}%
525   \exfs@unmerge@families{t}%
526   \exfs@merge@families{v}}

```

BEGIN added (cfr) - unmerge families

`\ifexfs@take` Define the macro needed to do the unmerges.  
`\exfs@unmergefamilies`

```

527 \newif\ifexfs@take
528 \newcommand*\exfs@unmerge@families[1]{%
529   \edef\exfs@tempf{#1}%
530   \edef\tempa{\expandafter\exfs@get@variants\f@family\@nil}%
531   \let\exfs@tempq\@empty
532   \edef\exfs@tempg{}}%
533   \exfs@taketrue

```

Check whether there are variants - if not do nothing

```

534   \ifx\tempa\@empty
535     \edef\exfs@tempq{}}%
536   \else

```

o/w go through the variants to find the one to delete

```

537     \loop

```

Get the next variant

```

538       \edef\exfs@tempn{\expandafter\exfs@next\tempa\@nil}%

```

See if the next variant is the thing we seek and, if so, eliminate it

```

539       \ifx\exfs@tempf\exfs@tempn
540         \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
541         \edef\exfs@tempq{\exfs@tempg\tempa}%
542         \exfs@takefalse

```

o/w save the next variant and move on if any variants remain

```

543       \else
544         \edef\exfs@tempg{\exfs@tempg\exfs@tempn}%
545         \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
546         \ifx\tempa\@empty% if there are no variants left, we're done
547           \edef\exfs@tempq{\exfs@tempg}%
548           \exfs@takefalse
549         \fi
550       \fi
551     \ifexfs@take % \fi yn \repeat
552   \repeat
553 \fi
554 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil \exfs@tempq}%
555 }

```

`\tstyle` These are simple unmerges, with no merging necessary.

`\lstyle`

```

556 \DeclareRobustCommand{\tstyle}{%% anniffiniedig tabular figures
557   \not@math@alphabet\tstyle\relax
558   \exfs@unmerge@families{2}}
559 \DeclareRobustCommand{\lstyle}{%% anniffiniedig lining figures (cf. command
      above)
560   \not@math@alphabet\lstyle\relax
561   \exfs@unmerge@families{j}}

```

`\tlstyle` Simple combinations for combined figure styles.

`\plstyle` Make a combined command for tabular lining

`\tostyle`

```

562 \DeclareRobustCommand{\tlstyle}{%% anniffiniedig
563   \lstyle\tstyle}

```

Proportional lining

```

564 \DeclareRobustCommand{\plstyle}{%% anniffiniedig
565   \lstyle\pstyle}

```

Tabular oldstyle ?!

```

566 \DeclareRobustCommand{\tostyle}{%% anniffiniedig
567   \ostyle\tstyle}

```

END added

`\sdefault` `si` is italic `sc`<sup>11</sup>. We use the original definition for the default and then set up rules  
`\sishape` for font shape changes which try `scit` and `scsl` before falling back to `si`.

```

568 \newcommand*{\sdefault}{si}% anniffiniedig

```

Well i brofi `si` & yna `scit` ond wn i ddim sut i wneud hon gyda'r stwff newydd  
 . . . I was going to deprecate the `si` macros, but the truth is they are much nicer  
 than having to combine macros for those cases when you really do want precisely  
 italic small-caps. They are also much more robust than somebody trying to force  
 things with `\fontshape{<si>}\selectfont`, so, on reflection, it seems better to  
 retain the interface, even if the implementation isn't as straightforward as I'd like.

```

569 \DeclareRobustCommand{\sishape}{%
570   \exfs@try@shapeshift{si}}

```

Kernel virtuals: `ulc` upper/lower case up upright. `nfssect` virtuals? or `nfssect-cfr`  
 virtuals? or? It would be better to try `si`, `scit` and `scsl`, but that doesn't seem  
 possible

```

571 \DeclareFontShapeChangeRule {n}{si}{scit}{scsl}% current; request (& trydedd);
      dewisiad cyntaf; ail ddewisiad
572 \DeclareFontShapeChangeRule {it}{si}{scit}{scsl}
573 \DeclareFontShapeChangeRule {sl}{si}{scit}{scsl}
574 \DeclareFontShapeChangeRule {sc}{si}{scit}{scsl}

```

Current shape is `si` => font support hasn't been updated

```

575 \DeclareFontShapeChangeRule {si}{sc} {si} {}

```

<sup>11</sup>That is, italic small-caps *was* `si`. These days, things are more complicated . . .

```

576 \DeclareFontShapeChangeRule {si}{it} {si} {}
577 \DeclareFontShapeChangeRule {si}{sl} {scsl} {si}
578 \DeclareFontShapeChangeRule {si}{scit} {scit} {si}% rhag ofn?!
579 \DeclareFontShapeChangeRule {si}{ulc} {it} {}
580 \DeclareFontShapeChangeRule {si}{up}{sc}{}

```

```

581 \ExplSyntaxOn

```

The need for overwriting can be avoided by changing the .fd files, but `compat` supports packages I don't know about<sup>12</sup> ...

```

582 \bool_if:NT \g_exfs_compat_bool
583 {
584   \DeclareFontShapeChangeRule {it}{sc}{si}{scsl}
585   \DeclareFontShapeChangeRule{sl}{sc}{scsl}{si}

```

Gofyn am italic etc. | Ask about italic etc. Sylwadau tebygol yma ... | Like comments here ...

```

586   \DeclareFontShapeChangeRule {sc}{it} {si} {scsl}
587   \DeclareFontShapeChangeRule {sc}{sl} {scsl} {si}
588   \DeclareFontShapeChangeRule {scsl}{it} {si} {scsl}
589 }
590 \ExplSyntaxOff

```

```

591 \DeclareFontShapeChangeRule {ui}{sc}{scit}{scsl}
592 \DeclareFontShapeChangeRule {ui}{scsl}{scsl}{scit}
593 \DeclareFontShapeChangeRule {ui}{it}{it}{ui}
594 \DeclareFontShapeChangeRule {ui}{ri}{ri}{ui}
595 \DeclareFontShapeChangeRule {ui}{up}{n}{}
596 \DeclareFontShapeChangeRule {ui}{ulc}{ui}{}

597 \DeclareFontShapeChangeRule {ri}{sc}{scit}{scsl}
598 \DeclareFontShapeChangeRule {ri}{scsl}{scsl}{scit}
599 \DeclareFontShapeChangeRule {ri}{it}{it}{ri}
600 \DeclareFontShapeChangeRule {ri}{ui}{ui}{ri}

```

Kernel virtuals: ulc upper/lower case up upright

```

601 \DeclareFontShapeChangeRule {ri}{up}{n}{}
602 \DeclareFontShapeChangeRule {ri}{ulc}{ri}{}

```

nfssex virtuals? or nfssex-cfr virtuals? or?

```

603 \DeclareFontShapeChangeRule {ol} {sc} {scol} {} % <- seiliedig ar nfssex-cfr-nfss.sty
   \scshape
604 \DeclareFontShapeChangeRule {ol} {ulc} {ol} {}
605 \DeclareFontShapeChangeRule {ol} {up} {ol} {}

606 \DeclareFontShapeChangeRule {scol} {sc} {scol} {}
607 \DeclareFontShapeChangeRule {scol} {ulc} {ol} {}
608 \DeclareFontShapeChangeRule {scol} {up} {scol} {}

609 \DeclareFontShapeChangeRule {u}{sc}{su}{} % <- seiliedig ar nfssex-cfr-nfss.sty
   \scshape

```

<sup>12</sup>Or haven't published? I haven't actually tried it with those.

```

610 \DeclareFontShapeChangeRule {su}{ulc}{u}{}
611 \DeclareFontShapeChangeRule {sc}{u}{su}{}
612 \DeclareFontShapeChangeRule {su}{u}{su}{}
613 \DeclareFontShapeChangeRule {su}{sc}{su}{}

```

BEGIN added (cfr)

cfr: is this how outline shapes should be handled?

```

\oldefault Outline
  \olshape
\scoldefault 614 \newcommand*{\oldefault}{ol}% anniffiniedig
  \scolshape 615 \DeclareRobustCommand{\olshape}{%% anniffiniedig
616   \exfs@try@shapeshift{ol}}
617 \newcommand*{\scoldefault}{scol}% anniffiniedig
618 \DeclareRobustCommand{\scolshape}{%% anniffiniedig
619   \exfs@try@shapeshift{scol}}

```

```

\udefault Underlined?? Fudge <- ??
  \ushape
\scudefault 620 \newcommand*{\udefault}{u}% anniffiniedig
  \scushape 621 \DeclareRobustCommand{\ushape}{%% anniffiniedig
622   \exfs@try@shapeshift{u}}
623 \newcommand*{\scudefault}{su}% anniffiniedig
624 \DeclareRobustCommand{\scushape}{%% anniffiniedig
625   \exfs@try@shapeshift{scu}}

```

```

\uidefault Upright and reverse italic
  \uishape
\ridefault 626 \newcommand*{\uidefault}{ui}% anniffiniedig
  \rishape 627 \DeclareRobustCommand{\uishape}{% anniffiniedig
628   \exfs@try@shapeshift{ui}}

```

Can i do this for reverse italic?

```

629 \newcommand*{\ridefault}{ri}% anniffiniedig
630 \DeclareRobustCommand{\rishape}{% anniffiniedig
631   \exfs@try@shapeshift{ri}}

```

END added BEGIN added (cfr) - merge width changes into series

`\exfs@merge@width` Previously dependent on incorrect series names.

```
632 \newcommand*{\exfs@merge@width}[1]{%
```

cfr-added

Dibynnodd y côd gwreiddiol ar *\*mc\** etc. & r'odd hynny'n anghywir

Instead of merging or unmerging cyclically, which means keeping track of everything, we split the current series (which requires some juggling, but hopefully less) and use the results.

```

633   \exfs@series@splitter{\f@series}%
634   \edef\exfs@temph{#1}%
635   \if\exfs@temph m\ifx\exfs@weight\@empty\else\let\exfs@temph\@empty\fi\fi
636   \if\exfs@weight m\ifx\exfs@temph\@empty\else\let\exfs@weight\@empty\fi\fi
637   \edef\exfs@series{\exfs@weight\exfs@temph}%

```

```

end cfr-added

638   \exfs@info{Trying \exfs@series}%
639   \exfs@try@series{\exfs@series}}

\regwidth ‘Regular’ width requires conditionally adding ‘m’.

640 \DeclareRobustCommand{\regwidth}{%% anniffiniedig
641   \not@math@alphabet\regwidth\relax

cfr altered

642   \exfs@merge@width{m}}

\nwdefault Condensed widths.
  \nwwidth
\cddefault 643 \newcommand*{\nwdefault}{c}% anniffiniedig
  \cdwidth 644 \DeclareRobustCommand{\nwwidth}{%% anniffiniedig ond rheolau
645   \not@math@alphabet\nwwidth\relax
\ecdefault 646 \exfs@merge@width{\nwdefault}}% neu \exfs@try@series ?
  \ecwidth 647 \newcommand*{\cddefault}{c}% anniffiniedig
\ucdefault 648 \DeclareRobustCommand{\cdwidth}{% anniffiniedig ond rheolau
  \ucwidth 649   \not@math@alphabet\cdwidth\relax
650   \exfs@merge@width{\cddefault}}% neu \exfs@try@series ?
651 \newcommand*{\ecdefault}{ec}% anniffiniedig
652 \DeclareRobustCommand{\ecwidth}{%% anniffiniedig ond rheolau
653   \not@math@alphabet\ecwidth\relax
654   \exfs@merge@width{\ecdefault}}% neu \exfs@try@series ?
655 \newcommand*{\ucdefault}{uc}% anniffiniedig
656 \DeclareRobustCommand{\ucwidth}{%% anniffiniedig
657   \not@math@alphabet\ucwidth\relax
658   \exfs@merge@width{\ucdefault}}

\etdefault Extended/expanded widths.
  \etwidth
\epdefault 659 \newcommand*{\etdefault}{x}% anniffiniedig
  \epwidth 660 \DeclareRobustCommand{\etwidth}{%% anniffiniedig
661   \not@math@alphabet\etwidth\relax
\exdefault 662 \exfs@merge@width{\etdefault}}% neu \exfs@try@series ?
  \exwidth 663 \newcommand*{\epdefault}{x}% anniffiniedig
\uxdefault 664 \DeclareRobustCommand{\epwidth}{%% anniffiniedig ond rheolau
  \uxwidth 665   \not@math@alphabet\epwidth\relax
666   \exfs@merge@width{\epdefault}}% neu \exfs@try@series ?
667 \newcommand*{\exdefault}{ex}% anniffiniedig
668 \DeclareRobustCommand{\exwidth}{%% anniffiniedig
669   \not@math@alphabet\exwidth\relax
670   \exfs@merge@width{\exdefault}}
671 \newcommand*{\uxdefault}{ux}% anniffiniedig
672 \DeclareRobustCommand{\uxwidth}{%% anniffiniedig
673   \not@math@alphabet\uxwidth\relax
674   \exfs@merge@width{\uxdefault}}

\mdwdefault Medium.
  \mdwidth
675 \newcommand*\mdwdefault{m}

```

```

676 \DeclareRobustCommand{\mdwidth}{%% anniffiniedig
677 \not@math@alphabet\mdwidth\relax
678 \exfs@merge@width{\mdwdefault}}

```

Posibl ond bydda i'n colli achosion yn siwr. | Possible but I'd lose cases for sure. Hefyd hoffwn i ddim dyfalu pa rheolau y bydden nhw eu dewis. | Also I wouldn't like to guess which rules they'll choose.

BEGIN added (cfr) merge weight changes into series

`\exfs@merge@weight` The pay off for setting up series splitting is that we can reuse the method here and, as in the case of width, the definition is greatly simplified<sup>13</sup>.

```

679 \newcommand*{\exfs@merge@weight}[1]{%
680 \exfs@series@splitter{\f@series}%

```

Save current series so we can test for change

```

681 \let\exfs@tempg\f@series
682 \def\exfs@temph{#1}%
683 \if\exfs@temph m\relax
684 \ifx\exfs@width\@empty\relax
685 \else
686 \let\exfs@temph\@empty
687 \fi
688 \fi
689 \edef\exfs@series{\exfs@temph\exfs@width}%
690 \ifx\exfs@temph\exfs@series
691 \exfs@info{Trying \exfs@series}%
692 \exfs@try@series{\exfs@series}%
693 \else
694 \exfs@info{Trying \exfs@series, favouring \exfs@weight}%
695 \exfs@try@series[\exfs@weight]{\exfs@series}% assume user wants to change
weight even if this changes back to the default width
696 \fi}

```

`\mbdefault` Ref.: sources2e.pdf and/or stripped code in base.

`\mbweight` The annotation 'anniffiniedig' indicates the macro is *not* defined by the kernel as  
`\bddefault` of 2024. The addition 'ond rheolau' means there are nonetheless relevant rules.  
`\bfweight` The comment 'dim byd i'w gael eu wneud yma' indicates that defining the default  
`\bdweight` is now sufficient and no additional font switch or text command is required.

```

697 \newcommand*{\mbdefault}{sb}% dim byd i'w gael ei wneud yma
698 \DeclareRobustCommand{\mbweight}{%% anniffiniedig
699 \not@math@alphabet\mbweight\relax
700 \exfs@merge@weight{\mbdefault}}
701 \newcommand*{\bddefault}{b}% dim byd i'w gael ei wneud yma
702 \DeclareRobustCommand{\bfweight}{%% anniffiniedig
703 \not@math@alphabet\bfweight\relax
704 \exfs@merge@weight{\bddefault}}
705 \DeclareRobustCommand{\bdweight}{%% anniffiniedig
706 \not@math@alphabet\bdweight\relax
707 \exfs@merge@weight{\bddefault}}

```

<sup>13</sup>At least if you don't look at the splitter code.



```

\mwdefault Regular, medium, default are all irregular, exceptional, fraught.
\mdweight
708 \newcommand*\mwdefault{m}
709 \DeclareRobustCommand{\mdweight}{%% anniffiniedig
710 \not@math@alphabet\mdweight\relax
711 \exfs@merge@weight{\mwdefault}}

\dbdefault Heavy weights.
\dbweight
712 \newcommand*\dbdefault{db}% anniffiniedig
\sbdefault
713 \DeclareRobustCommand{\dbweight}{%% anniffiniedig
\sbweight
714 \not@math@alphabet\dbweight\relax
\ebdefault
715 \exfs@merge@weight{\dbdefault}}
\ebweight
716 \newcommand*\sbdefault{sb}% anniffiniedig
\ubdefault
717 \DeclareRobustCommand{\sbweight}{%% anniffiniedig ond rheolau
\ubweight
718 \not@math@alphabet\sbweight\relax
719 \exfs@merge@weight{\sbdefault}}% neu \exfs@try@series ?
720 \newcommand*\ebdefault{eb}% anniffiniedig
721 \DeclareRobustCommand{\ebweight}{%% anniffiniedig ond rheolau
722 \not@math@alphabet\ebweight\relax
723 \exfs@merge@weight{\ebdefault}}% neu \exfs@try@series ?
724 \newcommand*\ubdefault{ub}% anniffiniedig
725 \DeclareRobustCommand{\ubweight}{%% anniffiniedig ond rheolau
726 \not@math@alphabet\ubweight\relax
727 \exfs@merge@weight{\ubdefault}}% neu \exfs@try@series ?

\lgdefault Light weights.
\lgweight
728 \newcommand*\lgdefault{l}% anniffiniedig
\eldefault
\elweight Note - use this if light is a variant weight, rather than a separate family
\uldefault
729 \DeclareRobustCommand{\lgweight}{%% anniffiniedig ond rheolau
730 \not@math@alphabet\lgweight\relax
731 \exfs@merge@weight{\lgdefault}}% neu \exfs@try@series ?
732 \newcommand*\eldefault{el}% anniffiniedig
733 \DeclareRobustCommand{\elweight}{%% anniffiniedig ond rheolau
734 \not@math@alphabet\elweight\relax
735 \exfs@merge@weight{\eldefault}}% neu \exfs@try@series ?
736 \newcommand*\uldefault{ul}% anniffiniedig
737 \DeclareRobustCommand{\ulweight}{%% anniffiniedig ond rheolau
738 \not@math@alphabet\ulweight\relax
739 \exfs@merge@weight{\uldefault}}% neu \exfs@try@series ?

END added Original

\dfshape Something simpler.
740 \let\dfshape\normalshape

\swshapedefault cfr: be' i wneud am hwn?
741 \newcommand*\swshapedefault{\itdefault}

 $\LaTeX$  ddim yn cynnwys \swstyle felly ...? |  $\LaTeX$  doesn't include \swstyle so
...?

```

```

742 \ExplSyntaxOn
743 \hook_gput_code:nnn {begindocument}{.}
744 {% compatibility with original nfs \swshape

```

Note this doesn't affect `\swashstyle` or `\textswash`

`\swshape` Conditional definition. We overwrite the kernel's definition either way. The `compat` option determines only with what we overwrite it.

```

745 \bool_if:NTF \g__exfs_compat_bool
746 {
747   \DeclareRobustCommand{\swshape}
748   {
749     \not@math@alphabet\swshape\relax
750     \swstyle\fontshape\swshapedefault\selectfont
751   }
752   \PackageWarning{nfssect-cfr}{
753     Overwriting ~ kernel ~ definition ~ of ~ \swshape \space (compat)
754   }
755 }{
756   \DeclareRobustCommand \swshape
757   {
758     \not@math@alphabet\swshape\relax
759     \exfs@swshape
760   }
761   \PackageWarning{nfssect-cfr}{
762     Overwriting ~ kernel ~ definition ~ of ~ \swshape \space (new)
763   }
764 }

```

`\textin` Conditional definition.

```

765 \@ifpackageloaded{hyperref}{
766   \expandafter\@ifl@t@r \csname ver@hyperref.sty\endcsname {2025/05/20}{
767     \DeclareTextFontCommand{\textin}{\instyle}
768   }{
769     \hook_gput_code:nnn { cmd/textin/before } { . }
770     {
771       \exfs@info{
772         Note ~ that ~ '\protect\textin' ~ is ~ defined ~ by ~ hyperref.\MessageBreak
773         Use ~ for ~ inferior ~ digits ~ will ~ yield ~ an\MessageBreak
774         undefined ~ command ~ error ~ in ~ document ~ font ~ encodings.\MessageBreak
775         Use ~ '\protect\textinf' ~ to ~ access ~ inferior ~ digits.\MessageBreak
776         Alternatively, ~ update ~ hyperref ~ to ~ 2025-05-20 ~ or ~ later
777       }
778     }
779   }
780 }{
781   \DeclareTextFontCommand{\textin}{\instyle}
782 }

783 }
784 \ExplSyntaxOff

```

`\textln` The annotation 'anniffiniedig' indicates the macro is *not* defined by the kernel as

`\textos`

`\textinf`

`\textsu`

`\textsi`

`\textdf`

of 2024.

```

785 \DeclareTextFontCommand{\textln}{\lnstyle}% anniffiniedig
786 \DeclareTextFontCommand{\textos}{\osstyle}% anniffiniedig
787 \DeclareTextFontCommand{\textinf}{\instyle}% anniffiniedig
788 \DeclareTextFontCommand{\textsu}{\sustyle}% anniffiniedig
789 \DeclareTextFontCommand{\textsi}{\sishape}% anniffiniedig
790 \DeclareTextFontCommand{\textdf}{\dfshape}% anniffiniedig

```

`\textsw` is already defined on newer kernels with essentially the same meaning as `nfssext` originally gave it, so we remove the definition here. However, the redefinition of `\swshape` means `\textsw` is effectively redefined, so the kernel definition is only technically retained.

BEGIN added (cfr)

```

\textti Families
\textlt
\textof 791 \DeclareTextFontCommand{\textti}{\tistyle}% anniffiniedig
\textalt 792 \DeclareTextFontCommand{\textlt}{\ltstyle}% anniffiniedig
\textreg 793 \DeclareTextFontCommand{\textof}{\ofstyle}% anniffiniedig % open-face
(or outline or blank) style
\emboss 794 \DeclareTextFontCommand{\textalt}{\altstyle}% anniffiniedig % alternative
\textorn style
\textqt 795 \DeclareTextFontCommand{\textreg}{\regstyle}% anniffiniedig % 'regular'
\textsh style
\texttm 796 \DeclareTextFontCommand{\emboss}{\embosstyle}% anniffiniedig
\texttv 797 \DeclareTextFontCommand{\textorn}{\ornamentalstyle}% anniffiniedig % intended
primarily for decorative initials etc.
798 \DeclareTextFontCommand{\textqt}{\qtstyle}% anniffiniedig
799 \DeclareTextFontCommand{\textsh}{\shstyle}% anniffiniedig % shadowed
style
800 \DeclareTextFontCommand{\texttm}{\tmstyle}% anniffiniedig
801 \DeclareTextFontCommand{\texttv}{\tvstyle}% anniffiniedig

```

`\textl` Families - figures

```

\texto 802 \DeclareTextFontCommand{\textl}{\lstyle}% anniffiniedig
\textp 803 \DeclareTextFontCommand{\texto}{\ostyle}% anniffiniedig
\textt 804 \DeclareTextFontCommand{\textp}{\pstyle}% anniffiniedig
\textpl 805 \DeclareTextFontCommand{\textt}{\tstyle}% anniffiniedig
\textpo 806 \DeclareTextFontCommand{\textpl}{\plstyle}% anniffiniedig
\texttl 807 \DeclareTextFontCommand{\textpo}{\postyle}% anniffiniedig
\textto 808 \DeclareTextFontCommand{\texttl}{\tlstyle}% anniffiniedig
809 \DeclareTextFontCommand{\textto}{\tostyle}% anniffiniedig

```

`\textol` Shapes

```

\textswash
\textu 810 \DeclareTextFontCommand{\textol}{\olshape}% anniffiniedig % outline
811 \DeclareTextFontCommand{\textswash}{\swashstyle}% anniffiniedig % an attempt
to improve on \textsw
\textscu 812 \DeclareTextFontCommand{\textu}{\ushape}% anniffiniedig % be' yw hwn?!
\textui <_ underlined?
813 \DeclareTextFontCommand{\textscu}{\scushape}% anniffiniedig
814 \DeclareTextFontCommand{\textui}{\uishape}% anniffiniedig % upright italic

```

```

815 \DeclareTextFontCommand{\textri}{\rshape}% anniffiniedig % reverse italic

\textnw Widths
\textcd 816 \DeclareTextFontCommand{\textnw}{\nwwidth}% anniffiniedig
\textec 817 \DeclareTextFontCommand{\textcd}{\cdwidth}% anniffiniedig
\textuc 818 \DeclareTextFontCommand{\textec}{\ecwidth}% anniffiniedig
\textet 819 \DeclareTextFontCommand{\textuc}{\ucwidth}% anniffiniedig
\textep 820 \DeclareTextFontCommand{\textet}{\etwidth}% anniffiniedig
\textex 821 \DeclareTextFontCommand{\textep}{\epwidth}% anniffiniedig
\textux 822 \DeclareTextFontCommand{\textex}{\exwidth}% anniffiniedig
\textrw 823 \DeclareTextFontCommand{\textux}{\uxwidth}% anniffiniedig
824 \DeclareTextFontCommand{\textrw}{\regwidth}% anniffiniedig

\textmb Weights
\textdb 825 \DeclareTextFontCommand{\textmb}{\mbweight}% anniffiniedig
\textbd 826 \DeclareTextFontCommand{\textdb}{\dbweight}% anniffiniedig
\textsb 827 \DeclareTextFontCommand{\textbd}{\bdweight}% new?
\texteb 828 \DeclareTextFontCommand{\textsb}{\sbweight}% anniffiniedig
\textub 829 \DeclareTextFontCommand{\texteb}{\ebweight}% anniffiniedig
\textlg 830 \DeclareTextFontCommand{\textub}{\ubweight}% anniffiniedig
\textel 831 \DeclareTextFontCommand{\textlg}{\lgweight}% anniffiniedig
\textul 832 \DeclareTextFontCommand{\textel}{\elweight}% anniffiniedig
833 \DeclareTextFontCommand{\textul}{\ulweight}% anniffiniedig

```

END added

BEGIN patch font initialisation for Latin Modern

Stop redefinition of bold if using Latin Modern as c<sub>l</sub>m. Kernel default only blocks redefinition for l<sub>m</sub>. Don't rely on cfr-lm internal macros as they may change without notice . . . . We don't need Dunhill, though, because it doesn't have bold of any kind. cfr-lm doesn't support using Quotation Sans as default or using e.g. serif as default sans, but there's nothing to stop somebody doing that so follow the kernel here even though it makes for a massive list<sup>14</sup>.

```

834 \patchcmd{\init@series@setup}{cmr,cmss,cmtt,lcms,lcmtt,lmr,lms,lmtt}{cmr,cmss,cmtt,lcms,l
835 \PackageWarning{nfssect-cfr}{%
836 Patching font initialisation macro for serif.%
837 }%
838 }{%
839 \PackageWarning{nfssect-cfr}{%
840 Failed to patch font initialisation macro for serif.%
841 }%
842 }
843 \patchcmd{\init@series@setup}{cmr,cmss,cmtt,lcms,lcmtt,lmr,lms,lmtt}{cmr,cmss,cmtt,lcms
844 \PackageWarning{nfssect-cfr}{%
845 Patching font initialisation macro for sans.%
846 }%
847 }{%
848 \PackageWarning{nfssect-cfr}{%
849 Failed to patch font initialisation macro for sans.%

```

<sup>14</sup>I know this will go off the page when typeset, but I have no idea whether I can safely insert line breaks into the patch and I shall scream if I break this again. (Pun fully intended.)

```

850 }%
851 }
852 \patchcmd{\init@series@setup}{\cmr,cmss,cmtt,lcms,lcmtt,lmr,lmss,lmtt}{\cmr,cmss,cmtt,lcms
853 \PackageWarning{nfssect-cfr}{%
854   Patching font initialisation macro for typewriter.%
855 }%
856 }{%
857 \PackageWarning{nfssect-cfr}{%
858   Failed to patch font initialisation macro for typewriter.%
859 }%
860 }

```

END

### 6.3 NFSS

This code was written for the *old* New Font Selection Scheme (NFSS). It should not generally be loaded on current or recent kernels.

`nfssect-cfr-nfss` (*pkg.*)

```

861 \NeedsTeXFormat{LaTeX2e}
862 \RequirePackage{svn-prov}
863 \ProvidesPackageSVN[\filebase-nfss.sty]{\$Id: nfssect-cfr.dtx 11042 2025-06-22
      22:34:34Z cfrees \$}[v1.3 \revinfo{] specially mangled by cfr; based on 2003/03/14
      v1.2 Experimental NFSS Extensions; for old NFSS]
864 \DefineFileInfoSVN

:cfr-added: use ifthen

865 \RequirePackage{ifthen}

:end-added

\exfs@tempa
\exfs@tempb
\exfs@tempf 866 \newcommand*\exfs@tempa{}
867 \newcommand*\exfs@tempb{}

:cfr-added: extra variable (\exfs@tempf)

868 \newcommand*\exfs@tempf{}

:end-added

\exfs@try@family

869 \newcommand*\exfs@try@family}[2] [] {%
870   \let\exfs@tempa\relax
871   \begingroup
872     \fontfamily{#2}\try@load@fontshape
873     \expandafter\ifx\csname\curr@fontshape\endcsname\relax
874     \edef\exfs@tempa{#1}%
875     \ifx\exfs@tempa@empty
876       \PackageWarning{nfssect}{%

```

```

877         Font family '\f@encoding/#2' not available\MessageBreak
878         Ignoring font switch}%
879     \else
880         \PackageInfo{nfssext}{%
881         Font family '\f@encoding/#2' not available\MessageBreak
882         Font family '\f@encoding/#1' tried instead}%
883         \exfs@try@family{#1}%
884     \fi
885 \else
886     \gdef\exfs@tempa{\fontfamily{#2}\selectfont}%
887 \fi
888 \endgroup
889 \exfs@tempa}

```

`\exfs@try@series` :cfr-added `\exfs@try@series`

```

890 \newcommand*{\exfs@try@series}[2] [] {%
891 \let\exfs@tempa\relax
892 \begingroup
893 \fontseries{#2}\try@load@fontshape
894 \expandafter\ifx\csname\curr@fontshape\endcsname\relax
895 \edef\exfs@tempa{#1}%
896 \ifx\exfs@tempa\@empty
897 \PackageWarning{nfssext-cfr}{%
898 Font series '\f@encoding/\f@family/#2' not available\MessageBreak
899 Ignoring font switch}%
900 \else
901 \PackageInfo{nfssext-cfr}{%
902 Font family '\f@encoding/\f@family/#2' not available\MessageBreak
903 Font family '\f@encoding/\f@family/#1' tried instead}%
904 \exfs@try@series{#1}%
905 \fi
906 \else
907 \gdef\exfs@tempa{\fontseries{#2}\selectfont}%
908 \fi
909 \endgroup
910 \exfs@tempa
911 }

```

:end-added

`\exfs@get@base`

`\exfs@get@variants`

`\exfs@next`

`\exfs@shift`

`\exfs@first`

`\exfs@part`

`\exfs@second`

```

912 \def\exfs@get@base#1#2#3#4\@nil{#1#2#3}
913 \def\exfs@get@variants#1#2#3#4\@nil{#4}
914 \def\exfs@next#1#2\@nil{#1}
915 \def\exfs@shift#1#2\@nil{#2}
916 \def\exfs@first#1#2\@nil{#1}
917 \def\exfs@part#1#2\@nil{#2}
918 \def\exfs@second#1#2#3\@nil{#2}

```

:end-added

```

\lnstyle
\osstyle
\infstyle 919 \DeclareRobustCommand{\lnstyle}{%
\instyle 920 \not@math@alphabet\lnstyle\relax
\instyle 921 \exfs@try@family[\expandafter\exfs@get@base\f@family\@nil]%
\sustyle 922 {\expandafter\exfs@get@base\f@family\@nil x}%
\swstyle 923 }
924 \DeclareRobustCommand{\osstyle}{%
925 \not@math@alphabet\osstyle\relax
926 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil j}}
927 \DeclareRobustCommand{\instyle}{%
928 \not@math@alphabet\instyle\relax
929 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil 0}}
930 \DeclareRobustCommand{\sustyle}{%
931 \not@math@alphabet\sustyle\relax
932 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil 1}}
933 \DeclareRobustCommand{\swstyle}{%
934 \not@math@alphabet\swstyle\relax
935 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil w}}

```

`\exfs@merge@families` :cfr-added - merge families

```

936 \newcommand*\exfs@merge@families[1]{%
937 \edef\exfs@tempf{#1}%
938 \edef\tempa{\expandafter\exfs@get@variants\f@family\@nil}%
939 \edef\tempo{2j}%
940 \let\exfs@tempq\@empty
941 \def\exfs@tempg{}%
942 \newif\ifadded
943 \addedfalse

```

check whether there are variants - if not just use the requested addition

```

944 \ifx\tempa\@empty
945 \edef\exfs@tempq{\exfs@tempf}%
946 \addedtrue
947 \else
948 \gdef\set{0,1,2,a,d,e,f,h,j,l,p,q,s,t,v,w}% these are the variants to
consider - the order here and in the font name is crucial
949 \ifx\tempo\exfs@tempf
950 \@for \xx:=\set \do {%

```

check whether there are variants left - if not set the ‘next variant’ to empty

```

951 \ifx\tempa\@empty
952 \let\exfs@tempn\@empty
953 \else

```

o/w get the next variant

```

954 \edef\exfs@tempn{\expandafter\exfs@next\tempa\@nil}%
955 \fi
956 \edef\tempt{2}%
957 \edef\tempj{j}%

```

if the next variant is 2 or j, ignore it

```

958     \ifx\exfs@tempn\tempt
959         \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
960     \fi
961     \ifx\exfs@tempn\tempj % if the next variant is j, ignore it
962         \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
963     \fi

```

see if the current value is either 2 or j and add it if so and if needed

```

964     \ifx\tempt\xx
965         \edef\exfs@tempg{\exfs@tempg\xx}%
966     \else
967         \ifx\tempj\xx % if the current value is j, we're done
968             \edef\exfs@tempq{\exfs@tempg\xx\tempa}%
969             \let\tempa\@empty
970             \addedtrue
971         \else

```

o/w see if the current value matches the next variant

```

972             \ifx\xx\exfs@tempn
973                 \edef\exfs@tempg{\exfs@tempg\xx}%
974                 \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
975             \fi
976         \fi
977     \fi
978 }%
979 \else
980     \@for \xx:=\set \do {%

```

check whether there are variants left and, if not, add the addition if needed

```

981     \ifx\tempa\@empty
982         \ifadded
983     \else
984         \edef\exfs@tempq{\exfs@tempg\exfs@tempf}%
985         \addedtrue
986     \fi
987     \else

```

o/w get the next variant

```

988         \edef\exfs@tempn{\expandafter\exfs@next\tempa\@nil}%

```

if the new token equals the next variant, combine whatever is saved in \exfs@tempg with whatever remains in \tempa

```

989     \ifx\exfs@tempn\exfs@tempf
990         \edef\exfs@tempq{\exfs@tempg\tempa}%
991         \addedtrue
992         \let\tempa\@empty
993     \else

```

o/w, if the current value matches the requested addition, add it in

```

994     \ifx\exfs@tempf\xx
995         \edef\exfs@tempq{\exfs@tempg\xx\tempa}%

```



```

996             \addedtrue
997             \let\tempa\@empty
998             \else

```

o/w, if the current value matches the next variant, shift

```

999             \ifx\exfs@tempn\xx
1000             \edef\exfs@tempg{\exfs@tempg\xx}%
1001             \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
1002             \fi
1003         \fi
1004     \fi
1005 \fi
1006 }%
1007 \fi
1008 \fi
1009 \ifx\exfs@tempq\@empty
1010     \PackageError{nfssex-cfr}{Something is wrong here. Ignoring font switching
command.}{}%
1011 \else
1012     \exfs@try@family{\expandafter\exfs@get@base\family\@nil \exfs@tempq}%
1013 \fi
1014 }

```

```

\pstyle
\ostyle
\postyle 1015 \DeclareRobustCommand{\pstyle}{% proportional figures
\mistyle 1016 \not@math@alphabet\pstyle\relax
1017 \exfs@merge@families{2}}
1018 \DeclareRobustCommand{\mistyle}{% titling/display
1019 \not@math@alphabet\mistyle\relax
1020 \exfs@merge@families{d}}
1021 \DeclareRobustCommand{\ostyle}{% oldstyle figures (cf. original osstyle
above)
1022 \not@math@alphabet\ostyle\relax
1023 \exfs@merge@families{j}}

combined command for proportional oldstyle

1024 \DeclareRobustCommand{\postyle}{%
1025 \not@math@alphabet\postyle\relax
1026 \exfs@merge@families{2j}}

```

```

\ltstyle note that this command is for use when the light version is a separate family rather
\ofstyle than a weight variant (e.g. when you've got light, light bold etc. as well as regular
\altstyle weights)
\regstyle
\embossstyle 1027 \DeclareRobustCommand{\ltstyle}{%
\ornamentalstyle 1028 \not@math@alphabet\ltstyle\relax
\swashstyle 1029 \exfs@merge@families{1}}
\shstyle let's hope there aren't any fonts with a light family *and* an outline/openface/blank
\qtstyle version
1030 \DeclareRobustCommand{\ofstyle}{%

```

```

1031 \not@math@alphabet\ofstyle\relax
1032 \exfs@merge@families{l}}
1033 \DeclareRobustCommand{\altstyle}{% alternative style
1034 \not@math@alphabet\altstyle\relax
1035 \exfs@merge@families{a}}
1036 \DeclareRobustCommand{\regstyle}{% ‘regular’ style
1037 \not@math@alphabet\regstyle\relax
1038 \exfs@try@family{\expandafter\exfs@get@base\f@family\@nil}}
1039 \DeclareRobustCommand{\embossstyle}{%
1040 \not@math@alphabet\embossstyle\relax
1041 \exfs@merge@families{e}}
1042 \DeclareRobustCommand{\ornamentalstyle}{% intended primarily for decorative
initial fonts etc.
1043 \not@math@alphabet\ornamentalstyle\relax
1044 \exfs@merge@families{p}}
1045 \DeclareRobustCommand{\qtstyle}{% quotation style (assumes sans)
1046 \not@math@alphabet\qtstyle\relax
1047 \sffamily
1048 \exfs@merge@families{q}}
1049 \DeclareRobustCommand{\shstyle}{%
1050 \not@math@alphabet\shstyle\relax
1051 \exfs@merge@families{h}}
1052 \DeclareRobustCommand{\swashstyle}{% an attempt to improve on \swstyle
1053 \not@math@alphabet\swashstyle\relax
1054 \exfs@merge@families{w}}

```

`\tmstyle` Macros to switch between monowidth and variable typewriter. These need to `\tvstyle` unmerge before merging. We need to unmerge sans as well as the other kind of typewriter.

```

1055 \DeclareRobustCommand{\tmstyle}{% monowidth typewriter
1056 \not@math@alphabet\tmstyle\relax
1057 \exfs@unmerge@families{s}%
1058 \exfs@unmerge@families{v}%
1059 \exfs@merge@families{t}}
1060 \DeclareRobustCommand{\tvstyle}{% variable width typewriter
1061 \not@math@alphabet\tvstyle\relax
1062 \exfs@unmerge@families{s}%
1063 \exfs@unmerge@families{t}%
1064 \exfs@merge@families{v}}

```

`\exfs@unmerge@families` :cfr-added - unmerge families

```

1065 \newcounter{taken}%
1066 \newcommand*\exfs@unmerge@families[1]{%
1067 \edef\exfs@tempf{#1}%
1068 \edef\tempa{\expandafter\exfs@get@variants\f@family\@nil}%
1069 \let\exfs@tempq\@empty
1070 \edef\exfs@tempg{}}%
1071 \setcounter{taken}{0}%

```

check whether there are variants - if not do nothing

```

1072 \ifx\tempa\@empty
1073 \edef\exfs@tempq{}}%

```

```

1074 \else
o/w go through the variants to find the one to delete
1075 \whiledo{\value{taken}<1}{%
get the next variant
1076 \edef\exfs@tempn{\expandafter\exfs@next\tempa\@nil}%
see if the next variant is the thing we seek and, if so, eliminate it
1077 \ifx\exfs@tempf\exfs@tempn
1078 \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
1079 \edef\exfs@tempq{\exfs@tempg\tempa}%
1080 \stepcounter{taken}%
o/w save the next variant and move on if any variants remain
1081 \else
1082 \edef\exfs@tempg{\exfs@tempg\exfs@tempn}%
1083 \edef\tempa{\expandafter\exfs@shift\tempa\@nil}%
1084 \ifx\tempa\@empty% if there are no variants left, we're done
1085 \edef\exfs@tempq{\exfs@tempg}%
1086 \stepcounter{taken}%
1087 \fi
1088 \fi
1089 }%
1090 \fi
1091 \exfs@try@family{\expandafter\exfs@get@base\family\@nil \exfs@tempq}%
1092 }

\tstyle
\lstyle
1093 \DeclareRobustCommand{\tstyle}{% tabular figures
1094 \not@math@alphabet\tstyle\relax
1095 \exfs@unmerge@families{2}}
1096 \DeclareRobustCommand{\lstyle}{% lining figures (cf. command above)
1097 \not@math@alphabet\lstyle\relax
1098 \exfs@unmerge@families{j}}

\tlstyle make a combined command for tabular lining
\plstyle
\tostyle
1099 \DeclareRobustCommand{\tlstyle}{%
1100 \lstyle\tstyle}

proportional lining
1101 \DeclareRobustCommand{\plstyle}{%
1102 \lstyle\pstyle}

tabular oldstyle ?!
1103 \DeclareRobustCommand{\tostyle}{%
1104 \ostyle\tstyle}

\sidefault :end-added si is italic sc
\sisshape

```

```

1105 \newcommand*\sdefault}{si}
1106 \DeclareRobustCommand{\sishape}{%
1107   \not@math@alphabet\sishape\relax
1108   \fontshape\sdefault\selectfont}

\oldefault :cfr-added - is this how outline shapes should be handled?
\olshape
\scoldefault 1109 \newcommand*\oldefault}{ol}
\scolshape 1110 \DeclareRobustCommand{\olshape}{%
1111   \not@math@alphabet\olshape\relax
1112   \fontshape\oldefault\selectfont}
1113 \newcommand*\scoldefault}{scol}
1114 \DeclareRobustCommand{\scolshape}{%
1115   \not@math@alphabet\scolshape\relax
1116   \fontshape\scoldefault\selectfont}

\udefault :fudge
\ushape
\scudefault 1117 \newcommand*\udefault}{u}
\scushape 1118 \DeclareRobustCommand{\ushape}{%
1119   \not@math@alphabet\ushape\relax
1120   \fontshape\udefault\selectfont}
1121 \newcommand*\scudefault}{su}
1122 \DeclareRobustCommand{\scushape}{%
1123   \not@math@alphabet\scushape\relax
1124   \fontshape\scudefault\selectfont}

\uidefault :upright italic
\uishape
\ridefault 1125 \newcommand*\uidefault}{ui}
\rishape 1126 \DeclareRobustCommand{\uishape}{%
1127   \not@math@alphabet\uishape\relax
1128   \fontshape\uidefault\selectfont}

:can i do this for reverse italic?

1129 \newcommand*\ridefault}{ri}
1130 \DeclareRobustCommand{\rishape}{%
1131   \not@math@alphabet\rishape\relax
1132   \fontshape\ridefault\selectfont}

:end-added

\exfs@merge@shape
1133 \newcommand*\exfs@merge@shape}[3]{%
1134   \edef\exfs@tempa{#1}%
1135   \edef\exfs@tempb{#2}%
1136   \ifx\f@shape\exfs@tempb
1137     \expandafter\ifx\c@name\f@encoding/\f@family/\f@series/#3\endcsname\relax
1138   \else
1139     \edef\exfs@tempa{#3}%
1140     \fi
1141   \fi
1142   \fontshape{\exfs@tempa}\selectfont}

```

`\exfs@font@width` :cfr-added - merge width changes into series

```

1143 \newcommand*{\exfs@font@width}{%
1144   \edef\exfs@tempf{\expandafter\exfs@first\f@series\@nil }%
1145   \edef\exfs@temppart{\expandafter\exfs@part\f@series\@nil }%
1146   \ifx\exfs@temppart\@empty
1147     \def\exfs@width{}
1148   \else
1149     \edef\exfs@temps{\expandafter\exfs@second\f@series\@nil }%
1150     \ifx\exfs@temps{b}
1151       \edef\exfs@width{\expandafter\exfs@part\exfs@temps\@nil }%
1152     \else
1153       \ifx\exfs@temps{l}
1154         \edef\exfs@width{\expandafter\exfs@part\exfs@temps\@nil }%
1155       \else
1156         \edef\exfs@width{\exfs@temppart}%
1157       \fi
1158     \fi
1159   \fi
1160   \exfs@width
1161 }

```

`\exfs@merge@width`

```

1162 \newcommand*{\exfs@merge@width}[1]{%
1163   \edef\exfs@temph{#1}%
1164   \edef\exfs@tempf{\expandafter\exfs@first\f@series\@nil }%
1165   \edef\exfs@temppart{\expandafter\exfs@part\f@series\@nil }%
1166   \def\tempb{b}%
1167   \def\templ{l}%
1168   \ifx\exfs@temppart\@empty
1169     \def\exfs@series{\expandafter\exfs@tempf\exfs@temph}%
1170   \else
1171     \edef\exfs@temps{\expandafter\exfs@second\f@series\@nil }%
1172     \ifx\exfs@temps\tempb
1173       \def\exfs@series{\expandafter\exfs@tempf\exfs@temps\exfs@temph}%
1174     \else
1175       \ifx\exfs@temps\templ
1176         \def\exfs@series{\expandafter\exfs@tempf\exfs@temps\exfs@temph}%
1177       \else
1178         \def\exfs@series{\expandafter\exfs@tempf\exfs@temph}%
1179       \fi
1180     \fi
1181   \fi
1182   \exfs@try@series{\exfs@series}%
1183 }
1184 %^^A \fontseries\exfs@series\selectfont}

```

`\exfs@unmerge@width`

```

1185 \newcommand*{\exfs@unmerge@width}{%
1186   \edef\exfs@tempf{\expandafter\exfs@first\f@series\@nil }%
1187   \edef\exfs@temppart{\expandafter\exfs@part\f@series\@nil }%
1188   \def\tempb{b}%
1189   \def\templ{l}%

```

```

1190 \ifx\exfs@temppart\@empty
1191   \def\exfs@series{\expandafter\exfs@tempf}%
1192 \else
1193   \edef\exfs@temps{\expandafter\exfs@second\f@series\@nil }%
1194   \ifx\exfs@temps\tempb
1195     \def\exfs@series{\expandafter\exfs@tempf\exfs@temps}%
1196   \else
1197     \ifx\exfs@temps\templ
1198       \def\exfs@series{\expandafter\exfs@tempf\exfs@temps}%
1199     \else
1200       \def\exfs@series{\expandafter\exfs@tempf}%
1201     \fi
1202   \fi
1203 \fi
1204 \exfs@try@series{\exfs@series}%
1205 }

\regwidth

1206 \DeclareRobustCommand{\regwidth}{%
1207   \not@math@alphabet\regwidth\relax
1208   \exfs@unmerge@width}

\nwdefault
\nwwidth
\cddefault 1209 \newcommand*{\nwdefault}{c}
\cdwidth 1210 \DeclareRobustCommand{\nwwidth}{%
1211   \not@math@alphabet\nwwidth\relax
\ecdefault 1212   \exfs@merge@width{\nwdefault}}
\ecwidth 1213 \newcommand*{\cddefault}{c}
\ucdefault 1214 \DeclareRobustCommand{\cdwidth}{%
1215   \not@math@alphabet\cdwidth\relax
1216   \exfs@merge@width{\cddefault}}
1217 \newcommand*{\ecdefault}{ec}
1218 \DeclareRobustCommand{\ecwidth}{%
1219   \not@math@alphabet\ecwidth\relax
1220   \exfs@merge@width{\ecdefault}}
1221 \newcommand*{\ucdefault}{uc}
1222 \DeclareRobustCommand{\ucwidth}{%
1223   \not@math@alphabet\ucwidth\relax
1224   \exfs@merge@width{\ucdefault}}

\etdefault
\etwidth
\epdefault 1225 \newcommand*{\etdefault}{x}
\epwidth 1226 \DeclareRobustCommand{\etwidth}{%
1227   \not@math@alphabet\etwidth\relax
\exdefault 1228   \exfs@merge@width{\etdefault}}
\exwidth 1229 \newcommand*{\epdefault}{x}
\uxdefault 1230 \DeclareRobustCommand{\epwidth}{%
1231   \not@math@alphabet\epwidth\relax
1232   \exfs@merge@width{\epdefault}}
1233 \newcommand*{\exdefault}{ex}
1234 \DeclareRobustCommand{\exwidth}{%

```

```

1235 \not@math@alphabet\exwidth\relax
1236 \exfs@merge@width{\exdefault}}
1237 \newcommand*{\uxdefault}{ux}
1238 \DeclareRobustCommand{\uxwidth}{%
1239 \not@math@alphabet\uxwidth\relax
1240 \exfs@merge@width{\uxdefault}}

```

`\exfs@merge@weight` :cfr-added merge weight changes into series

```

1241 \newcommand*{\exfs@merge@weight}[1]{%
1242 \edef\exfs@tempg{#1}%
1243 \edef\exfs@tempf{\expandafter\exfs@first\f@series\@nil }%
1244 \edef\exfs@temppart{\expandafter\exfs@part\f@series\@nil }%
1245 \def\templ{1}%
1246 \def\tempb{b}%

```

:case when there's no second part, so the single character must be the weight and should be replaced

```

1247 \ifx\exfs@temppart\@empty
1248 \def\exfs@series{\expandafter\exfs@tempg}%

```

:case when there's a second part

```

1249 \else

```

:get first character of second part

```

1250 \edef\exfs@temps{\expandafter\exfs@second\f@series\@nil }%
1251 \edef\exfs@tempw{\expandafter\exfs@part\exfs@temps\@nil }%

```

:is the first character b? if so, it is part of the weight and should be replaced

```

1252 \ifx\exfs@temps\tempb
1253 \def\exfs@series{\expandafter\exfs@tempg\exfs@tempw}%
1254 \else

```

:is the first character l? if so, it is part of the weight and should be replaced

```

1255 \ifx\exfs@temps\templ
1256 \def\exfs@series{\expandafter\exfs@tempg\exfs@tempw}%
1257 \else

```

:o/w the first character is part of the width and should be retained

```

1258 \def\exfs@series{\expandafter\exfs@tempg\exfs@temppart}%
1259 \fi
1260 \fi
1261 \fi

```

```

1262 \ifx\exfs@tempg\exfs@series
1263 \exfs@try@series{\exfs@series}%
1264 \else
1265 \exfs@try@series[\exfs@tempg]{\exfs@series}% assume user wants to
change weight even if this changes back to the default width
1266 \fi
1267 }

```

```

1268 % \end{macrocode}
1269 % \end{macro}
1270 % \begin{macro}{\mbdefault,\mbweight,\bddefault,\bfweight,\bdweight}
1271 % \begin{macrocode}
1272 \newcommand*{\mbdefault}{mb}
1273 \DeclareRobustCommand{\mbweight}{%
1274 \not@math@alphabet\mbweight\relax
1275 \exfs@merge@weight{\mbdefault}}

\dbdefault Heavy weights.
\dbweight
\sbdefault 1276 \newcommand*{\dbdefault}{db}
\sbweight 1277 \DeclareRobustCommand{\dbweight}{%
1278 \not@math@alphabet\dbweight\relax
\ebdefault 1279 \exfs@merge@weight{\dbdefault}}
\ebweight 1280 \newcommand*{\sbdefault}{sb}
\ubdefault 1281 \DeclareRobustCommand{\sbweight}{%
\ubweight 1282 \not@math@alphabet\sbweight\relax
1283 \exfs@merge@weight{\sbdefault}}
1284 \newcommand*{\ebdefault}{eb}
1285 \DeclareRobustCommand{\ebweight}{%
1286 \not@math@alphabet\ebweight\relax
1287 \exfs@merge@weight{\ebdefault}}
1288 \newcommand*{\ubdefault}{ub}
1289 \DeclareRobustCommand{\ubweight}{%
1290 \not@math@alphabet\ubweight\relax
1291 \exfs@merge@weight{\ubdefault}}
1292 \newcommand*{\lgdefault}{l}

\lgdefault note - use this if light is a variant weight, rather than a separate family
\lgweight
\eldefault 1293 \DeclareRobustCommand{\lgweight}{%
1294 \not@math@alphabet\lgweight\relax
\elweight 1295 \exfs@merge@weight{\lgdefault}}
\uldefault 1296 \newcommand*{\eldefault}{el}
\ulweight 1297 \DeclareRobustCommand{\elweight}{%
1298 \not@math@alphabet\elweight\relax
1299 \exfs@merge@weight{\eldefault}}
1300 \newcommand*{\uldefault}{ul}
1301 \DeclareRobustCommand{\ulweight}{%
1302 \not@math@alphabet\ulweight\relax
1303 \exfs@merge@weight{\uldefault}}

:end-added

\itshape redefinition
\scshape
\upshape 1304 \DeclareRobustCommand{\itshape}{%
1305 \not@math@alphabet\itshape\mathit
\dfshape 1306 \exfs@merge@shape{\itdefault}{\scdefault}{\sdefault}}

original :cfr-altered: \scshape

1307 \DeclareRobustCommand{\scshape}{%
1308 \not@math@alphabet\scshape\relax

```



```

1309 \def\tempu{u}%
1310 \def\tempo{ol}%
1311 \ifx\f@shape\tempu
1312 \exfs@merge@shape{\scdefault}{\udefault}{\scudefault}%
1313 \else
1314 \ifx\f@shape\tempo
1315 \exfs@merge@shape{\scdefault}{\oldefault}{\scoldefault}%
1316 \else
1317 \exfs@merge@shape{\scdefault}{\itdefault}{\sidedefault}%
1318 \fi
1319 \fi
1320 }

:end-altered

1321 \DeclareRobustCommand{\upshape}{%
1322 \not@math@alphabet\upshape\relax
1323 \exfs@merge@shape{\updefault}{\sidedefault}{\scdefault}}
1324 \DeclareRobustCommand{\dfshape}{%
1325 \not@math@alphabet\dfshape\relax
1326 \fontshape\shapedefault\selectfont}

\swshapedefault
\swshape
1327 \newcommand*{\swshapedefault}{\itdefault}
1328 \DeclareRobustCommand{\swshape}{%
1329 \not@math@alphabet\swshape\relax
1330 \swstyle\fontshape\swshapedefault\selectfont}

\textln
\textos
\textin 1331 \DeclareTextFontCommand{\textln}{\lnstyle}
\textsu 1332 \DeclareTextFontCommand{\textos}{\osstyle}
\textsi 1333 \DeclareTextFontCommand{\textin}{\instyle}
\textdf 1334 \DeclareTextFontCommand{\textsu}{\sustyle}
\textsw 1335 \DeclareTextFontCommand{\textsi}{\sishape}
1336 \DeclareTextFontCommand{\textdf}{\dfshape}
1337 \DeclareTextFontCommand{\textsw}{\swshape}

:cfr-added

\textti Families
\textlt 1338 \DeclareTextFontCommand{\textti}{\tistyle}
\textof 1339 \DeclareTextFontCommand{\textlt}{\ltstyle}
\textalt 1340 \DeclareTextFontCommand{\textof}{\ofstyle} % open-face (or outline or
\textreg blank) style
\emboss 1341 \DeclareTextFontCommand{\textalt}{\altstyle} % alternative style
\textorn 1342 \DeclareTextFontCommand{\textreg}{\regstyle} % ‘‘regular’’ style
\textqt 1343 \DeclareTextFontCommand{\emboss}{\embossstyle}
\textsh 1344 \DeclareTextFontCommand{\textorn}{\ornamentalstyle} % intended primarily
\texttm for decorative initials etc.
\texttv 1345 \DeclareTextFontCommand{\textqt}{\qtstyle}
1346 \DeclareTextFontCommand{\textsh}{\shstyle} % shadowed style
1347 \DeclareTextFontCommand{\texttm}{\tmstyle}
1348 \DeclareTextFontCommand{\texttv}{\tvstyle}

```

```

\textl Families - figures
\texto
\textp 1349 \DeclareTextFontCommand{\textl}{\lstyle}
\textt 1350 \DeclareTextFontCommand{\textp}{\ostyle}
\textt 1351 \DeclareTextFontCommand{\textp}{\pstyle}
\textpl 1352 \DeclareTextFontCommand{\textt}{\tstyle}
\textpo 1353 \DeclareTextFontCommand{\textpl}{\plstyle}
\texttl 1354 \DeclareTextFontCommand{\textpo}{\postyle}
\textto 1355 \DeclareTextFontCommand{\texttl}{\tlstyle}
1356 \DeclareTextFontCommand{\textto}{\tostyle}

\textol Shapes
\textswash 1357 \DeclareTextFontCommand{\textol}{\olshape} % outline
\textu 1358 \DeclareTextFontCommand{\textswash}{\swashstyle} % an attempt to improve
\textscu on \textsw
\textui 1359 \DeclareTextFontCommand{\textu}{\ushape}
\textri 1360 \DeclareTextFontCommand{\textscu}{\scushape}
1361 \DeclareTextFontCommand{\textui}{\uishape} % upright italic
1362 \DeclareTextFontCommand{\textri}{\rishape} % reverse italic

\textnw Widths
\textcd 1363 \DeclareTextFontCommand{\textnw}{\nwidth}
\textec 1364 \DeclareTextFontCommand{\textcd}{\cdwidth}
\textuc 1365 \DeclareTextFontCommand{\textec}{\ecwidth}
\textet 1366 \DeclareTextFontCommand{\textuc}{\ucwidth}
\textep 1367 \DeclareTextFontCommand{\textet}{\etwidth}
\textex 1368 \DeclareTextFontCommand{\textep}{\epwidth}
\textux 1369 \DeclareTextFontCommand{\textex}{\exwidth}
\textrw 1370 \DeclareTextFontCommand{\textux}{\uxwidth}
1371 \DeclareTextFontCommand{\textrw}{\regwidth}

\textmb Weights
\textdb 1372 \DeclareTextFontCommand{\textmb}{\mbweight}
\textbd 1373 \DeclareTextFontCommand{\textdb}{\dbweight}
\textsb 1374 \DeclareTextFontCommand{\textsb}{\sbweight}
\texteb 1375 \DeclareTextFontCommand{\texteb}{\ebweight}
\textub 1376 \DeclareTextFontCommand{\textub}{\ubweight}
\textlg 1377 \DeclareTextFontCommand{\textlg}{\lgweight}
\textel 1378 \DeclareTextFontCommand{\textel}{\elweight}
\textul 1379 \DeclareTextFontCommand{\textul}{\ulweight}

end-added

```

## Change History

SVN6140

General: Fixes a bug which prevented `\tmstyle` and `\tvstyle` working correctly if

the current font was not a serif family. (Especially problematic in Beamer where `\normalfont` cannot be used as a

workaround, but annoying elsewhere.) . . . . .	1	width. . . . .	11
Provides something a bit closer to real documentation. . . . .	1	Split <code>nfssect-cfr.sty</code> into <code>nfssect-cfr{,-nfss,-nnfss}.sty</code> . . . . .	11
2008-10-26		<code>nfssect-cfr-nfss</code> : Conditionally override kernel rules affecting switches to upright/small-caps.italic etc. . . . .	29
General: First public release as part of <code>cfr-lm</code> . . . . .	1	Unconditionally add a bunch of shape change rules for shapes unsupported by the kernel - I don't *think* these should be problematic: if the current or requested shape is unsupported by the kernel, surely it can't be problematic to support that shape? . . . . .	29
2008-12-22		<code>\swshape</code> : Conditionally overwrite <code>\swshape</code> to take account of default setting. This is not for any package I know of on CTAN, but the original code used <code>\textsw</code> . . . . .	34
General: Updated version released standalone. . . . .	1	<code>\ubweight</code> : Make <code>\mbdefault sb</code> (duplicating <code>\sbdefault</code> ) as I can't come up with anything better. . . . .	33
2010-07-17		v1.1	
General: There should be no changes for the end user except that in certain cases it is possible that line-breaks may be altered if microtype is in use due to the enhanced support included for variant font families. . . . .	11	<code>nfssect-cfr</code> : Fix grouping cock up. . . . .	16
<code>\Microtype@Hook</code> : Add microtype support for variants. . . . .	16	v1.2	
<code>\qtstyle</code> : Improve <code>\ofstyle</code> . . . . .	26	<code>nfssect-cfr</code> : Workaround to allow use of encoding subset declarations in font definition files, even if somebody tries to use a font package with an older format. . . . .	14
v0.0		v1.3	
<code>nfssect-cfr</code> : Update for NNFS. . . . .	11	<code>\textin</code> : All <code>\textin</code> if hyperref is new enough to avoid conflict. . . . .	34
v1.0		v6140	
<code>compat</code> : Add option <code>compat</code> . More aggressive/backwards compatible with <code>compat</code> . . . . .	12	General: Extend documentation somewhat. . . . .	11
<code>debug</code> : Add option <code>debug</code> . . . . .	12	<code>\tvstyle</code> : Modify <code>\tmstyle</code> and <code>\tvstyle</code> to unmerge sans and other typewriter before merging appropriate variant. . . . .	26
<code>\exfs@merge@width</code> : Do not depend on incorrect series names, which are no longer supported. . . . .	30		
<code>\exfs@series@splitter</code> : Rewritten as kernel no longer supports erroneous <code>m</code> . . . . .	22		
<code>force</code> : Add option <code>force</code> . Load old file/incompatible with <code>force</code> . . . . .	12		
<code>nfssect-cfr</code> : Behaviour depends on kernel version and options. On newer kernels, quite conservative/less compatible by default. Fully compatible on older kernels. . . . .	11		
So <code>nfssect-cfr</code> merging is now limited to family, weight and			

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>Symbols</b>	
<code>\/</code> .....	134
<code>\@DeclareEncodingSubset</code> .....	117
<code>\@DeclareEncodingSubset@copi</code> .....	<u>117</u> , 120
<code>\@empty</code> .....	225, 256, 363, 364, 365, 372, 373, 405, 408, 415, 416, 431, 443, 454, 459, 471, 531, 534, 546, 635, 636, 684, 686, 875, 896, 940, 944, 951, 952, 969, 981, 992, 997, 1009, 1069, 1072, 1084, 1146, 1168, 1190, 1247
<code>\@for</code> .....	414, 442, 950, 980
<code>\@ifl@t@r</code> .....	16, 42, 766
<code>\@ifpackageloaded</code> .....	160, 765
<code>\@ifundefined</code> .....	7, 167
<code>\@nfssectcfr@digonnewfalse</code> ...	12, 19
<code>\@nfssectcfr@digonnewtrue</code> .....	6
<code>\@nil</code> .....	135, 142, 153, 317, 320, 326, 331, 349, 350, 351, 352, 353, 354, 355, 357, 358, 371, 378, 384, 385, 388, 391, 395, 398, 402, 418, 421, 424, 436, 450, 463, 474, 500, 530, 538, 540, 545, 554, 912, 913, 914, 915, 916, 917, 918, 921, 922, 926, 929, 932, 935, 938, 954, 959, 962, 974, 988, 1001, 1012, 1038, 1068, 1076, 1078, 1083, 1091, 1144, 1145, 1149, 1151, 1154, 1164, 1165, 1171, 1186, 1187, 1193, 1243, 1244, 1250, 1251
<code>\@roman</code> .....	132, 144, 151
<code>\__exfs_set:n</code> .....	<u>125</u> , 129
<b>A</b>	
<code>\addedfalse</code> .....	943
<code>\addedtrue</code> ...	946, 970, 985, 991, 996
<code>\altstyle</code> ....	5, <u>486</u> , 794, <u>1027</u> , 1341
<b>B</b>	
<code>\bddefault</code> .....	<u>697</u> , 1270
<code>\bdweight</code> .....	7, <u>697</u> , 827, 1270
<code>\begin</code> .....	1270, 1271
<code>\begingroup</code> .....	133, 150, 220, 248, 283, 307, 871, 892
<code>\bfweight</code> .....	7, <u>697</u> , 1270
<code>\bool_if:N</code> .....	111
<code>\bool_if:NT</code> .....	94, 582
<code>\bool_if:NTF</code> .....	89, 745
<code>\bool_new:N</code> .....	27
<code>\bool_set_false:N</code> .....	104
<code>\bool_set_true:N</code> .....	108
<b>C</b>	
<code>\catcode</code> .....	134
<code>\cddefault</code> .....	<u>643</u> , <u>1209</u>
<code>\cdwidth</code> .....	6, <u>643</u> , 817, <u>1209</u> , 1364
<code>\char</code> .....	154
<code>compat (opt.)</code> .....	8, 30
<code>\cs_if_exist:NTF</code> .....	87
<code>\cs_if_exist_use:c</code> .....	70
<code>\cs_if_free:NTF</code> .....	113
<code>\cs_new_protected_nopar:Nn</code> .....	125
<code>\cs_set_eq:NN</code> .....	129
<code>\csname</code> .....	132, 144, 151, 186, 200, 223, 271, 766, 873, 894, 1137
<code>\curr@fontshape</code> .....	186, 197, 198, 201, 203, 205, 207, 213, 215, 223, 302, 873, 894
<b>D</b>	
<code>\dbdefault</code> .....	<u>712</u> , <u>1276</u>
<code>\dbweight</code> ....	7, <u>712</u> , 826, <u>1276</u> , 1373
<code>debug (opt.)</code> .....	<i>ii</i> , <u>34</u>
<code>\DeclareEncodingSubset</code> ...	4, 113, <u>115</u>
<code>\DeclareFontShapeChangeRule</code> .	571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 584, 585, 586, 587, 588, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613
<code>\DeclareMicrotypeVariants</code> .....	158
<code>\DeclareRobustCommand</code> ..	143, 382, 386, 389, 393, 396, 477, 480, 483, 486, 489, 492, 495, 498, 501, 504, 507, 511, 514, 517, 522, 556, 559, 562, 564, 566, 569, 615, 618, 621, 624, 627, 630, 640, 644, 648, 652, 656, 660, 664, 668, 672, 676, 698, 702, 705, 709, 713, 717, 721, 725, 729, 733, 737, 747, 756, 919,

- 924, 927, 930, 933, 1015, 1018,  
 1021, 1024, 1027, 1030, 1033,  
 1036, 1039, 1042, 1045, 1049,  
 1052, 1055, 1060, 1093, 1096,  
 1099, 1101, 1103, 1106, 1110, 1114,  
 1118, 1122, 1126, 1130, 1206,  
 1210, 1214, 1218, 1222, 1226,  
 1230, 1234, 1238, 1273, 1277,  
 1281, 1285, 1289, 1293, 1297,  
 1301, 1304, 1307, 1321, 1324, 1328
- `\DeclareTextFontCommand` . . . . .  
 . . . . . 767, 781, 785, 786, 787,  
 788, 789, 790, 791, 792, 793,  
 794, 795, 796, 797, 798, 799,  
 800, 801, 802, 803, 804, 805,  
 806, 807, 808, 809, 810, 811,  
 812, 813, 814, 815, 816, 817, 818,  
 819, 820, 821, 822, 823, 824,  
 825, 826, 827, 828, 829, 830,  
 831, 832, 833, 1331, 1332, 1333,  
 1334, 1335, 1336, 1337, 1338,  
 1339, 1340, 1341, 1342, 1343,  
 1344, 1345, 1346, 1347, 1348,  
 1349, 1350, 1351, 1352, 1353,  
 1354, 1355, 1356, 1357, 1358,  
 1359, 1360, 1361, 1362, 1363,  
 1364, 1365, 1366, 1367, 1368,  
 1369, 1370, 1371, 1372, 1373,  
 1374, 1375, 1376, 1377, 1378, 1379
- `\DeclareTextOrnament` . . . . . 131
- `\def` . . . . . 115, 132, 136,  
 137, 138, 139, 140, 142, 157, 270,  
 349, 350, 351, 352, 353, 354,  
 355, 356, 364, 365, 370, 406,  
 682, 912, 913, 914, 915, 916, 917,  
 918, 941, 1147, 1166, 1167, 1169,  
 1173, 1176, 1178, 1188, 1189, 1191,  
 1195, 1198, 1200, 1245, 1246,  
 1248, 1253, 1256, 1258, 1309, 1310
- `\DefineFileInfoSVN` . . . . . 4, 178, 864
- `\dfshape` . . . . . 6, 740, 790, 1304, 1336
- `\do` . . . . . 414, 442, 950, 980
- E**
- `\ebdefault` . . . . . 712, 1276
- `\ebweight` . . . . . 7, 712, 829, 1276, 1375
- `\ecdefault` . . . . . 643, 1209
- `\ecwidth` . . . . . 6, 643, 818, 1209, 1365
- `\edef` . . . . . 151, 224, 243, 250, 255,  
 271, 276, 284, 285, 357, 358,  
 371, 372, 373, 374, 377, 401,  
 402, 404, 409, 418, 421, 424,  
 427, 430, 435, 436, 446, 450,  
 452, 457, 462, 463, 529, 530,  
 532, 535, 538, 540, 541, 544,  
 545, 547, 634, 637, 689, 874,  
 895, 937, 938, 939, 945, 954,  
 956, 957, 959, 962, 965, 968,  
 973, 974, 984, 988, 990, 995,  
 1000, 1001, 1067, 1068, 1070,  
 1073, 1076, 1078, 1079, 1082,  
 1083, 1085, 1134, 1135, 1139,  
 1144, 1145, 1149, 1151, 1154, 1156,  
 1163, 1164, 1165, 1171, 1186, 1187,  
 1193, 1242, 1243, 1244, 1250, 1251
- `\eldefault` . . . . . 728, 1293
- `\else` . . . . . 149, 192, 214, 229, 235, 247,  
 254, 260, 275, 289, 292, 300,  
 323, 329, 334, 339, 344, 360,  
 361, 362, 363, 365, 373, 374,  
 411, 417, 428, 433, 441, 445, 449,  
 455, 460, 473, 536, 543, 635,  
 636, 685, 693, 879, 885, 900,  
 906, 947, 953, 966, 971, 979,  
 983, 987, 993, 998, 1011, 1074,  
 1081, 1138, 1148, 1152, 1155,  
 1170, 1174, 1177, 1192, 1196, 1199,  
 1249, 1254, 1257, 1264, 1313, 1316
- `\elweight` . . . . . 7, 728, 832, 1293, 1378
- `\emboss` . . . . . 5, 791, 1338
- `\embossstyle` . . . . . 5, 486, 796, 1027, 1343
- `\end` . . . . . 1268, 1269
- `\endcsname` . . . . . 132, 144, 151, 186, 197,  
 200, 201, 203, 205, 223, 251,  
 271, 286, 287, 766, 873, 894, 1137
- `\endgroup` . . . . . 141,  
 155, 239, 267, 295, 347, 888, 909
- `\epdefault` . . . . . 659, 1225
- `\epwidth` . . . . . 6, 659, 821, 1225, 1368
- `\etdefault` . . . . . 659, 1225
- `\etwidth` . . . . . 6, 659, 820, 1225, 1367
- `\exdefault` . . . . . 659, 1225
- `\exf@try@family` . . . . . 317
- `\exfs@addedfalse` . . . . . 407
- `\exfs@addedtrue` 410, 432, 447, 453, 458
- `\exfs@base@family` . . . . . 142, 144, 146, 151
- `\exfs@check@cx` 359, 360, 361, 362, 370
- `\exfs@first` . . . . . 349,  
 357, 371, 912, 1144, 1164, 1186, 1243
- `\exfs@font@width` . . . . . 1143
- `\exfs@get@base` . . . . . 142,  
 317, 320, 326, 331, 349, 384,  
 385, 388, 391, 395, 398, 474,  
 500, 554, 912, 921, 922, 926,  
 929, 932, 935, 1012, 1038, 1091

- \exfs@get@variants . . . . . 244, 250, 251, 284, 285, 286,  
.. 349, 402, 530, 912, 938, 1068
- \exfs@info . 189, 198, 213, 215, 221,  
230, 236, 245, 252, 273, 277,  
302, 368, 403, 638, 691, 694, 771
- \exfs@merge@families . . . . . 309,  
312, 315, 336, 341, 345, 399,  
479, 482, 485, 488, 491, 494,  
497, 503, 506, 510, 513, 516,  
521, 526, 936, 1017, 1020, 1023,  
1026, 1029, 1032, 1035, 1041,  
1044, 1048, 1051, 1054, 1059, 1064
- \exfs@merge@shape . . . . . 1133, 1306, 1312, 1315, 1317, 1323
- \exfs@merge@weight . . . . . 679,  
700, 704, 707, 711, 715, 719, 723,  
727, 731, 735, 739, 1241, 1279,  
1283, 1287, 1291, 1295, 1299, 1303
- \exfs@merge@width . . . . . 632, 642,  
646, 650, 654, 658, 662, 666,  
670, 674, 678, 1162, 1212, 1216,  
1220, 1224, 1228, 1232, 1236, 1240
- \exfs@next . . . . . 349,  
418, 450, 538, 912, 954, 988, 1076
- \exfs@nextvariant . . . . . 416,  
418, 420, 423, 434, 450, 451, 461
- \exfs@normalise . . . . . 196, 249
- \exfs@part . . . . . 349, 912, 1145,  
1151, 1154, 1165, 1187, 1244, 1251
- \exfs@reserved . . . . . 255, 256
- \exfs@second . . . . .  
.. 349, 912, 1149, 1171, 1193, 1250
- \exfs@series .. 637, 638, 639, 689,  
690, 691, 692, 694, 695, 1169,  
1173, 1176, 1178, 1182, 1184, 1191,  
1195, 1198, 1200, 1204, 1248,  
1253, 1256, 1258, 1262, 1263, 1265
- \exfs@series@splitter . 356, 633, 680
- \exfs@shift . . . . . 349, 358, 378,  
421, 424, 436, 463, 540, 545,  
912, 959, 962, 974, 1001, 1078, 1083
- \exfs@split@orndef . . . . . 135, 152
- \exfs@swfamily . . . . . 288, 293, 305
- \exfs@swshape . . . . . 281, 759
- \exfs@takefalse . . . . . 542, 548
- \exfs@taketrue . . . . . 533
- \exfs@targetseries . . . . 242, 253, 268
- \exfs@targetshape . . . . .  
.. 271, 272, 276, 277, 278, 279
- \exfs@targetsw . . . . 282, 290, 296,  
301, 306, 324, 330, 335, 340, 345
- \exfs@tempa . . . . . 140, 154, 179,  
219, 224, 225, 237, 240, 243,  
244, 250, 251, 284, 285, 286,  
287, 308, 310, 313, 316, 318,  
321, 371, 372, 373, 375, 866,  
870, 874, 875, 886, 889, 891,  
895, 896, 907, 910, 1134, 1139, 1142
- \exfs@tempa@fake . . . . . 285
- \exfs@tempb 151, 153, 179, 866, 1135, 1136
- \exfs@tempf . . . . .  
179, 529, 539, 866, 937, 945,  
949, 984, 989, 994, 1067, 1077,  
1144, 1164, 1169, 1173, 1176, 1178,  
1186, 1191, 1195, 1198, 1200, 1243
- \exfs@tempg . . . . . 406, 427, 430,  
435, 446, 452, 457, 462, 532,  
541, 544, 547, 681, 941, 965,  
968, 973, 984, 990, 995, 1000,  
1070, 1079, 1082, 1085, 1242,  
1248, 1253, 1256, 1258, 1262, 1265
- \exfs@temp h . . . . . 634, 635,  
636, 637, 682, 683, 686, 689,  
690, 1163, 1169, 1173, 1176, 1178
- \exfs@tempn . . . . . 538, 539,  
544, 952, 954, 958, 961, 972,  
988, 989, 999, 1076, 1077, 1082
- \exfs@temp part 1145, 1146, 1156, 1165,  
1168, 1187, 1190, 1244, 1247, 1258
- \exfs@tempq . . . . . 405, 409,  
430, 446, 452, 457, 471, 474,  
531, 535, 541, 547, 554, 940,  
945, 968, 984, 990, 995, 1009,  
1012, 1069, 1073, 1079, 1085, 1091
- \exfs@temps . . . . . 1149, 1150,  
1151, 1153, 1154, 1171, 1172, 1173,  
1175, 1176, 1193, 1194, 1195,  
1197, 1198, 1250, 1251, 1252, 1255
- \exfs@tempw . . . . . 1251, 1253, 1256
- \exfs@try@family . . . . . 218,  
319, 384, 388, 391, 395, 398,  
474, 500, 554, 869, 921, 926,  
929, 932, 935, 1012, 1038, 1091
- \exfs@try@series . . . . . 241, 639,  
646, 650, 654, 662, 666, 692,  
695, 719, 723, 727, 731, 735,  
739, 890, 1182, 1204, 1263, 1265
- \exfs@try@shapeshift . . . . . 270,  
570, 616, 619, 622, 625, 628, 631
- \exfs@unmerge@families . 519, 520,  
524, 525, 528, 558, 561, 1057,  
1058, 1062, 1063, 1065, 1095, 1098
- \exfs@unmerge@width . . . . 1185, 1208
- \exfs@unmergefamilies . . . . . 527
- \exfs@variants . . . . 402, 403, 408,  
415, 418, 421, 424, 430, 431, 436,

- 443, 450, 452, 454, 457, 459, 463  
`\exfs@vartomerge` .....  
 .... 401, 409, 413, 446, 451, 456  
`\exfs@weight` ..... 357, 359, 360,  
 361, 362, 364, 365, 372, 373,  
 375, 376, 635, 636, 637, 694, 695  
`\exfs@weight:` ..... 368  
`\exfs@weighta` ..... 374, 376  
`\exfs@width` 358, 363, 364, 365, 368,  
 371, 372, 373, 378, 379, 684,  
 689, 1147, 1151, 1154, 1156, 1160  
`\exfs@widtha` ..... 377, 379  
`\expandafter` .....  
 .. 132, 142, 144, 152, 153, 185,  
 186, 200, 223, 317, 320, 325,  
 330, 357, 358, 371, 378, 384,  
 385, 388, 391, 395, 398, 402,  
 418, 421, 424, 436, 450, 463,  
 474, 500, 530, 538, 540, 545,  
 554, 766, 873, 894, 921, 922,  
 926, 929, 932, 935, 938, 954,  
 959, 962, 974, 988, 1001, 1012,  
 1038, 1068, 1076, 1078, 1083,  
 1091, 1137, 1144, 1145, 1149, 1151,  
 1154, 1164, 1165, 1169, 1171, 1173,  
 1176, 1178, 1186, 1187, 1191, 1193,  
 1195, 1198, 1200, 1243, 1244,  
 1248, 1250, 1251, 1253, 1256, 1258  
`\ExpandArgs` ..... 69  
`\ExplLoaderFileDate` ..... 16  
`\ExplSyntaxOff` ... 130, 188, 590, 784  
`\ExplSyntaxOn` ..... 25, 182, 581, 742  
`\exwidth` ..... 6, 659, 822, 1225, 1369
- F**
- `\f@encoding` .....  
 . 136, 221, 227, 231, 232, 236,  
 250, 258, 262, 263, 278, 284,  
 877, 881, 882, 898, 902, 903, 1137  
`\f@family` ..... 137, 142,  
 250, 258, 262, 263, 278, 284,  
 308, 310, 313, 316, 317, 318,  
 320, 321, 326, 331, 384, 385,  
 388, 391, 395, 398, 402, 474,  
 500, 530, 554, 898, 902, 903,  
 921, 922, 926, 929, 932, 935,  
 938, 1012, 1038, 1068, 1091, 1137  
`\f@series` . 138, 202, 244, 245, 252,  
 278, 284, 633, 680, 681, 1137,  
 1144, 1145, 1149, 1164, 1165, 1171,  
 1186, 1187, 1193, 1243, 1244, 1250  
`\f@shape` . 139, 202, 250, 258, 262,  
 263, 272, 273, 277, 1136, 1311, 1314
- `\fi` .... 21, 109, 156, 173, 194, 210,  
 211, 212, 216, 234, 238, 265,  
 266, 269, 280, 291, 294, 303,  
 328, 333, 338, 343, 346, 366,  
 367, 380, 419, 422, 425, 437,  
 438, 439, 448, 464, 465, 466,  
 467, 469, 470, 475, 549, 550,  
 551, 553, 635, 636, 687, 688,  
 696, 884, 887, 905, 908, 955,  
 960, 963, 975, 976, 977, 986,  
 1002, 1003, 1004, 1005, 1007,  
 1008, 1013, 1087, 1088, 1090,  
 1140, 1141, 1157, 1158, 1159, 1179,  
 1180, 1181, 1201, 1202, 1203,  
 1259, 1260, 1261, 1266, 1318, 1319  
`\filebase` ..... 3, 177, 863  
`\fmtversion` ..... 42  
`\fontfamily` 222, 237, 325, 330, 872, 886  
`\fontseries` ..... 253, 893, 907, 1184  
`\fontshape` ..... 279,  
 290, 311, 314, 319, 325, 336,  
 341, 750, 1108, 1112, 1116, 1120,  
 1124, 1128, 1132, 1142, 1326, 1330  
force (opt.) ..... 7, 37
- G**
- `\g@addto@macro` ..... 170  
`\g__exfs_compat_bool` 30, 94, 582, 745  
`\g__exfs_force_bool` ..... 37, 89  
`\g_msg_module_name_prop` ..... 26  
`\gdef` . 135, 237, 253, 290, 324, 330,  
 335, 340, 345, 412, 886, 907, 948  
`\global` ..... 169, 185
- H**
- `\hook_gput_code:nnn` .....  
 ..... 85, 118, 183, 743, 769
- I**
- `\if` .. 313, 316, 318, 321, 359, 360,  
 361, 362, 364, 365, 372, 373,  
 420, 423, 426, 429, 635, 636, 683  
`\if@nfssectcfr@digonnew` ... 5, 15, 23  
`\ifadded` ..... 942, 982  
`\ifcsname` .....  
 197, 201, 203, 205, 251, 286, 287  
`\ifexfs@added` ..... 399  
`\ifexfs@debug` ..... 24, 190  
`\ifexfs@take` ..... 527  
`\IfFileExists` ..... 8  
`\IfFormatAtLeastT` ..... 105  
`\IfFormatAtLeastTF` ..... 42, 43, 66  
`\ifnum` ..... 107  
`\IfValueTF` ..... 51

- `\ifx` . . . . . 144, 223, 225, 244, 256,  
 272, 296, 310, 363, 408, 413,  
 415, 434, 443, 451, 456, 461,  
 471, 534, 539, 546, 635, 636,  
 684, 690, 873, 875, 894, 896,  
 944, 949, 951, 958, 961, 964,  
 967, 972, 981, 989, 994, 999,  
 1009, 1072, 1077, 1084, 1136,  
 1137, 1146, 1150, 1153, 1168,  
 1172, 1175, 1190, 1194, 1197,  
 1247, 1252, 1255, 1262, 1311, 1314  
`\infstyle` . . . . . 5, 382, 919  
`\init@series@setup` . 87, 834, 843, 852  
`\instyle` 5, 382, 767, 781, 787, 919, 1333  
`\itdefault` . . . . . 741, 1306, 1317, 1327  
`\itshape` . . . . . 4, 1304
- K**
- `\keys_define:nn` . . . . . 28  
`\keys_set:nn` . . . . . 127
- L**
- `\l_exfs_tmpa_bool` . . 27, 104, 108, 111  
`\let` . . . . . 117, 120, 168, 185,  
 219, 242, 282, 306, 308, 364,  
 365, 372, 373, 376, 379, 392,  
 405, 416, 431, 454, 459, 531,  
 635, 636, 681, 686, 740, 870,  
 891, 940, 952, 969, 992, 997, 1069  
`\lgdefault` . . . . . 728, 1292, 1293  
`\lgweight` . . . . . 7, 728, 831, 1293, 1377  
`\lnstyle` . . . . . 5, 382, 785, 919, 1331  
`\loop` . . . . . 537  
`\lstyle` . . . . . 5, 556, 563,  
 565, 802, 1093, 1100, 1102, 1349  
`\ltstyle` . . . . . 5, 486, 792, 1027, 1339
- M**
- `\mathit` . . . . . 1305  
`\mbdefault` . . . . . 697, 1270, 1272, 1275  
`\mbweight` . . . . . 7,  
 697, 825, 1270, 1273, 1274, 1372  
`\mdwdefault` . . . . . 675  
`\mdweight` . . . . . 7, 708  
`\mdwidth` . . . . . 6, 675  
`\MessageBreak` . . . . .  
 . . . . . 53, 57, 59, 146, 162, 163,  
 198, 206, 208, 227, 231, 245,  
 258, 262, 273, 277, 298, 772,  
 773, 774, 775, 877, 881, 898, 902  
`\Microtype@Hook` . . . . . 157  
`\msg_line_number:` . . . . . 75, 81  
`\msg_new:nnn` . . . . . 73, 79
- `\msg_warning:nn` . . . . . 91, 96  
`\mwdefault` . . . . . 708
- N**
- `\newcommand` . . . . . 131,  
 179, 180, 181, 189, 196, 218, 241,  
 281, 305, 400, 528, 568, 614,  
 617, 620, 623, 626, 629, 632,  
 643, 647, 651, 655, 659, 663,  
 667, 671, 675, 679, 697, 701,  
 708, 712, 716, 720, 724, 728,  
 732, 736, 741, 866, 867, 868,  
 869, 890, 936, 1066, 1105, 1109,  
 1113, 1117, 1121, 1125, 1129, 1133,  
 1143, 1162, 1185, 1209, 1213,  
 1217, 1221, 1225, 1229, 1233,  
 1237, 1241, 1272, 1276, 1280,  
 1284, 1288, 1292, 1296, 1300, 1327  
`\newcounter` . . . . . 1065  
`\NewDocumentCommand` . . . . . 49  
`\newif` . . . . . 5, 24, 399, 527, 942  
`nfssect-cfr (pkg.)` . . . . . 1  
`nfssect-cfr-nfss (pkg.)` . . . . . 861  
`nfssect-cfr-nfss (pkg.)` . . . . . 175  
`\nfssectcfr@MT@Hook` . . . . . 157  
`\nfssectset` . . . . . 4, 129  
`\normalfont` . . . . . 204  
`\normalshape` . . . . . 740  
`\not@math@alphabet` . . . . . 276,  
 383, 387, 390, 394, 397, 478,  
 481, 484, 487, 490, 493, 496,  
 499, 502, 505, 508, 512, 515,  
 518, 523, 557, 560, 641, 645,  
 649, 653, 657, 661, 665, 669,  
 673, 677, 699, 703, 706, 710,  
 714, 718, 722, 726, 730, 734,  
 738, 749, 758, 920, 925, 928,  
 931, 934, 1016, 1019, 1022, 1025,  
 1028, 1031, 1034, 1037, 1040,  
 1043, 1046, 1050, 1053, 1056,  
 1061, 1094, 1097, 1107, 1111,  
 1115, 1119, 1123, 1127, 1131, 1207,  
 1211, 1215, 1219, 1223, 1227,  
 1231, 1235, 1239, 1274, 1278,  
 1282, 1286, 1290, 1294, 1298,  
 1302, 1305, 1308, 1322, 1325, 1329  
`\nwdefault` . . . . . 643, 1209  
`\nwwidth` . . . . . 6, 643, 816, 1209, 1363
- O**
- `\ofstyle` . . . . . 5, 486, 793, 1027, 1340  
`\oldefault` . . . . . 614, 1109, 1315  
`\olshape` . . . . . 6, 614, 810, 1109, 1357



- options:
- compat ..... 8, 30
  - debug ..... 11, 34
  - force ..... 7, 37
- \ornament ..... 5, 131
- \ornamentalstyle 5, 486, 797, 1027, 1344
- \osstyle ..... 5, 382, 786, 919, 1332
- \ostyle 5, 477, 567, 803, 1015, 1104, 1350
- P**
- \PackageError .... 52, 206, 472, 1010
- \PackageInfo ..... 193, 880, 901
- \PackageWarning .....  
 ..... 121, 145, 161, 191, 226,  
 257, 261, 297, 752, 761, 835,  
 839, 844, 848, 853, 857, 876, 897
- \patch@level ..... 107
- \patchcmd ..... 834, 843, 852
- \plstyle ..... 5, 562, 806, 1099, 1353
- \postyle ..... 5, 477, 807, 1015, 1354
- \ProcessKeyOptions ..... 49
- \ProcessKeysOptions ..... 48, 51, 59
- \prop\_gput:Nnn ..... 26
- \protect ..... 56, 57, 59, 61, 772, 775
- \providecommand ..... 42, 69
- \pstyle 5, 477, 565, 804, 1015, 1102, 1351
- Q**
- \qtstyle ..... 5, 486, 798, 1027, 1345
- R**
- \regstyle .... 5, 486, 795, 1027, 1342
- \regwidth .... 6, 640, 824, 1206, 1371
- \relax 144, 186, 219, 223, 242, 244,  
 272, 276, 282, 296, 306, 322,  
 383, 387, 390, 394, 397, 478,  
 481, 484, 487, 490, 493, 496,  
 499, 502, 505, 508, 512, 515,  
 518, 523, 557, 560, 641, 645,  
 649, 653, 657, 661, 665, 669,  
 673, 677, 683, 684, 699, 703,  
 706, 710, 714, 718, 722, 726,  
 730, 734, 738, 749, 758, 870,  
 873, 891, 894, 920, 925, 928,  
 931, 934, 1016, 1019, 1022, 1025,  
 1028, 1031, 1034, 1037, 1040,  
 1043, 1046, 1050, 1053, 1056,  
 1061, 1094, 1097, 1107, 1111,  
 1115, 1119, 1123, 1127, 1131, 1137,  
 1207, 1211, 1215, 1219, 1223,  
 1227, 1231, 1235, 1239, 1274,  
 1278, 1282, 1286, 1290, 1294,  
 1298, 1302, 1308, 1322, 1325, 1329
- \repeat ..... 551, 552
- \RequirePackage .. 2, 9, 11, 18, 47,  
 68, 72, 92, 98, 101, 176, 862, 865
- \revinfo ..... 3, 177, 863
- \rdefault ..... 626, 1125
- \rshape ..... 6, 626, 815, 1125, 1362
- \rule ..... 148
- S**
- \sbdefault ..... 712, 1276
- \sbweight .... 7, 712, 828, 1276, 1374
- \scdefault 1306, 1312, 1315, 1317, 1323
- \scoldefault ..... 614, 1109, 1315
- \scolshape ..... 6, 614, 1109
- \scshape ..... 4, 603, 609, 1304
- \scudefault ..... 620, 1117, 1312
- \scushape .... 6, 620, 813, 1117, 1360
- \selectfont 154, 200, 202, 237, 253,  
 279, 290, 326, 331, 750, 886,  
 907, 1108, 1112, 1116, 1120, 1124,  
 1128, 1132, 1142, 1184, 1326, 1330
- \seriesdefault ..... 202
- \set ..... 412, 414, 442, 948, 950, 980
- \setcounter ..... 1071
- \sffamily ..... 509, 1047
- \shapedefault ..... 202, 1326
- \shstyle ..... 5, 486, 799, 1027, 1346
- \sidefault . 568, 1105, 1306, 1317, 1323
- \sishape ..... 6, 568, 789, 1105, 1335
- \space ..... 252, 277, 753, 762
- \stepcounter ..... 1080, 1086
- \string ..... 121, 153
- \sustyle ..... 5, 382, 788, 919, 1334
- \swshapedefault ..... 741, 1327
- \swashstyle ... 5, 486, 811, 1027, 1358
- \swdefault ..... 284, 290
- \swshape .. 4, 5, 6, 744, 745, 1327, 1337
- \swshapedefault ..... 314,  
 319, 325, 336, 741, 750, 1327, 1330
- \swstyle 6, 382, 514, 750, 919, 1052, 1330
- T**
- \tempa 530, 534, 538, 540, 541, 545,  
 546, 938, 944, 951, 954, 959,  
 962, 968, 969, 974, 981, 988,  
 990, 992, 995, 997, 1001, 1068,  
 1072, 1076, 1078, 1079, 1083, 1084
- \tempb 1166, 1172, 1188, 1194, 1246, 1252
- \tempj ..... 957, 961, 967
- \templ 1167, 1175, 1189, 1197, 1245, 1255
- \tempo .. 404, 413, 939, 949, 1310, 1314
- \tempt ..... 956, 958, 964

